Specifications



Post fixing device galvanized steel post diam.max 215mm load 100kg for PLM54/64

NSYSFP400

Main

Range	Thalassa
Accessory / Separate Part Category	Fixing accessory
Product Or Component Type	Post fixing device
Device Application	Multi-purpose
Enclosure Nominal Dimensions	- H: 530 mm W: 430 mm D: 200 mm - H: 647 mm W: 436 mm D: 250 mm
Mounting Location	Outdoor installations on a post Rear of enclosure
Range Compatibility	Thalassa Thalassa PLM
Device Composition	fixing elements 2 support rail 2 strip

Complementary

Material	Galvanised steel
Fixing Mode	By fixing element - on a post location
Permanent Permissible Load	100 kg
Height	45 mm
Width	395 mm
Depth	32.5 mm
Diameter	215 mm

Packing Units

V	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.7 cm
Package 1 Width	14.0 cm
Package 1 Length	40.0 cm
Package 1 Weight	2.13 kg
Unit Type Of Package 2	PAM
Number Of Units In Package 2	100
Package 2 Height	120 cm
Package 2 Width	100 cm

Package 2 Length	90 cm
Package 2 Weight	146 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Eq

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations