NSYTVR125

Vertical uprights height 1250mm. zinc-coated steel. Supply: 2 standard uprights.



Main Range Thalassa Accessory / separate Mounting accessory part category **Product or Component** Technical upright Type Anwendung Multi-purpose Nennmaße des 49.21 in (1250 mm) Gehäuses Mounting Support Direct fixing on the rear inserts Step slide Thalassa PLA Range compatibility Device composition 2 upright

steel

Complementary

Surface Finish	Zinc coated	
Fixing mode	Bosses inserts M8 - rear of enclosure	
Adjustment	Adjustable in depth every 25 mm with caged nuts Adjustable in height every 2.5 mm with quarter-turn nuts	
Height	Nominal 49.21 in (1250 mm) Real 44.29 in (1125 mm)	
Width	1.77 in (45 mm)	
Depth	1.34 in (34 mm)	
Thickness	0.08 in (2 mm)	
Cut-out dimensions	11 x 13 mm	

Material

Ordering and shipping details

2002C ENCLOSURE SYSTEMS ASSESSORIES
80036-ENCLOSURE SYSTEMS ACCESSORIES
ES1
3606480185069
1
7.72 lb(US) (3.5 kg)
No
FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.57 in (4 cm)
Package 1 width	2.36 in (6 cm)
Package 1 Length	44.29 in (112.5 cm)

Offer Sustainability

[™] REACh Declaration
REACH Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Yes
Yes
₽¥Yes
China RoHS Declaration
Product Environmental Profile

Contractual warranty

147 4	40 11
Warranty	18 months
	To monate