

# Product data sheet

Specifications



## Spacial SF transparent door - 1400x600 mm

NSYSFD146T

 To be discontinued on: Sep 30, 2024

 To be discontinued

### Main

|                                    |   |
|------------------------------------|---|
| Range                              | Spacial   |
| Accessory / Separate Part Category | Enclosure accessory   |
| Product Or Component Type          | Door  |
| Application                        | Multi-purpose   |
| For Enclosure Nominal Dimensions   | -   |
| Mounting Location                  | Side<br>Front   |
| Range Compatibility                | Spacial Spacial SF  |
| Device Composition                 | 1 door<br>1 lock with handle and 5 mm double bar insert<br>1 locking bar system 4 points<br>4 hinges<br>4 locking bar catches |
| Quantity Per Set                   | Set of 1  |

### Complementary

|                   |  |
|-------------------|--|
| Material          | Door: Securit glass<br>Door: sheet steel |
| Colour            | Grey (RAL 7035)                          |
| Surface Finish    | Epoxy-polyester powder                   |
| Lock Type         | Lock 5 mm double bar                     |
| Number Of Locks   | 1  |
| Door Type         | External transparent                     |
| Door Opening Side | Reversible (120 °)                       |
| Height            | 1400 mm nominal:                         |
| Width             | 600 mm nominal:                          |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type Of Package 1       | PCE      |
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 5.5 cm   |
| Package 1 Width              | 57.5 cm  |
| Package 1 Length             | 140.0 cm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                              |          |
|------------------------------|----------|
| Package 1 Weight             | 14.0 kg  |
| Unit Type Of Package 2       | P2M      |
| Number Of Units In Package 2 | 10       |
| Package 2 Height             | 42.0 cm  |
| Package 2 Width              | 200.0 cm |
| Package 2 Length             | 120.0 cm |
| Package 2 Weight             | 172.0 kg |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

|                          |   |
|--------------------------|---|
| Reach Regulation         | <a href="#">REACH Declaration</a>   |
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile      | No need of specific recycling operations  |