

PanelSeT SF double plain doors - 2000x1000 mm

NSYSFD20102D

Main

Range	PanelSeT
Accessory / separate part categor	Enclosure accessory
product or component type	Door
Application	Multi-purpose
For enclosure nominal dimensions	-
mounting location	Front
Range compatibility	PanelSeT PanelSeT SF
Device composition	1 lock with handle and 5 mm double bar insert 1 locking bar system 4 points 2 door 1 blocking system 2 reinforcement frame 8 hinges
Quantity per set	Set of 1

Complementary

Material	Sheet steel
Colour	Grey (RAL 7035)
Surface finish	Epoxy-polyester powder
lock type	Lock 5 mm double bar
Number of locks	1
Door type	External plain
Door opening side	Reversible (120 °)
Maximum load	60 kg/m²
Height	Nominal: 2000 mm
Width	Nominal: 1000 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.89 cm
Package 1 Width	53.34 cm
Package 1 Length	199.39 cm
Package 1 Weight	41.73 kg

Unit Type of Package 2	PAL
Number of Units in Package 2	10
Package 2 Height	63 cm
Package 2 Width	210 cm
Package 2 Length	120 cm
Package 2 Weight	448 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations