NSYS3D101030DP

Spacial S3D dbl plain door with mount.plate. H1000xW1000xD300 IP55 IK10 RAL7035.



Spacial
Spacial S3D
Multi-purpose
Compact enclosure
39.37 in (1000 mm)
39.37 in (1000 mm)
11.81 in (300 mm)
Solid
Plain
Standard
Wall-mounting
1 body 2 cable gland plate 2 door with lock 1 mounting plate

Complementary

Body type	Single piece body	
	Gutter-shaped front rail double sheet thickness	
Number of doors	Front face 2	
Door opening side	Reversible 120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges	
	Cable gland plate by screws	
	Mounting plate by fixing element	
Material	Enclosure steel	
	Mounting plate galvanised steel	
Surface finish	Enclosure epoxy-polyester powder	
Color	Enclosure Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	GL	
	BV	
	LR	
	UL	
	DNV	
	cUL	
Net Weight	141.10 lb(US) (64 kg)	

Environment

IK degree of protection	IK10 IEC 62262
IP degree of protection	IP55 IEC 60529

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480160325
Nbr. of units in pkg.	1
Package weight(Lbs)	141.10 lb(US) (64.0 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	40.31 in (102.4 cm)	
Package 1 width	40.39 in (102.6 cm)	
Package 1 Length	13.94 in (35.4 cm)	

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
₫Yes
☐ China RoHS Declaration
Product Environmental Profile

Contractual warranty

Warranty	18 months	