NSYS3D3420P

Spacial S3D plain door with mount.plate. H300xW400xD200 IP66 IK10 RAL7035.





Main

Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	11.81 in (300 mm)
Enclosure nominal width	15.75 in (400 mm)
Enclosure nominal depth	7.87 in (200 mm)
Door type	Solid
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	body mounting plate door with lock cable gland plate

Complementary

Body type	Single piece body Gutter-shaped front rail double sheet thickness	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 mm double-bar lock	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure steel Mounting plate galvanised steel	
Surface finish	Enclosure epoxy-polyester powder	
Color	Enclosure Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	DNV LR BV UL CUL GL	
Net Weight	14.99 lb(US) (6.8 kg)	_

Environment

NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP66 IEC 60529

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480159657
Nbr. of units in pkg.	1
Package weight(Lbs)	14.95 lb(US) (6.782 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	9.76 in (24.8 cm)	
Package 1 width	12.44 in (31.6 cm)	
Package 1 Length	16.38 in (41.6 cm)	

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
₫Yes
☐ China RoHS Declaration
Product Environmental Profile

Contractual warranty

· · · · · · · · · · · · · · · · · · ·	
Warranty	18 months