# **NSYS3D4420**

Spacial S3D plain door w/o mount.plate. H400xW400xD200 IP66 IK10 RAL7035.





#### Main

Spacial
Spacial S3D
Multi-purpose
Compact enclosure
15.75 in (400 mm)
15.75 in (400 mm)
7.87 in (200 mm)
Solid
Without mounting plate
Standard
Wall-mounting
1 body 1 door 1 lock 1 cable gland plate

#### Complementary

Complementary	
Body type	Gutter-shaped front rail double sheet thickness Single piece body
Number of doors	Front face 1
Door opening side	Reversible 120 °)
Lock type	3 mm double-bar lock
Accessibility for operation	Front
Removable parts	Door by hinges Cable gland plate by screws
Material	steel
Surface finish	Epoxy-polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	LR GL UL DNV BV cUL
Net Weight	14.33 lb(US) (6.5 kg)

### Environment

NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP66 IEC 60529

## Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480159572
Nbr. of units in pkg.	1
Package weight(Lbs)	14.33 lb(US) (6.5 kg)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	16.26 in (41.3 cm)	
Package 1 width	16.46 in (41.8 cm)	
Package 1 Length	9.76 in (24.8 cm)	

### Offer Sustainability

Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
₫Yes
☐ China RoHS Declaration
Product Environmental Profile

### Contractual warranty

Warranty	18 months