

Main

Spacial
Spacial S3HF
Industrial Application
Compact enclosure
31.50 in (800 mm)
23.62 in (600 mm)
11.81 in (300 mm)
Solid
Without mounting plate
Without gland plate
Wall-mounting
1 body 1 door with lock 1 mounting plate

Complementary

Body type	Single piece body
Number of doors	Front face 1
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Body aluzinc
Surface finish	Epoxy-polyester powder
Color	Gray RAL 7035)
Standards	IEC 60529
Net Weight	70.55 lb(US) (32 kg)

Environment

Electromagnetic compatibility	EMC immunity	
IK degree of protection	IK10 IEC 62262	
IP degree of protection	IP55	

Ordering and shipping details

Category	80035-ENCLOSURE SYSTEMS FLOOR MOUNT	
Discount Schedule	ES1	
GTIN	3606480212789	
Nbr. of units in pkg.	1	
Package weight(Lbs)	70.55 lb(US) (32.0 kg)	
Returnability	No	
Country of origin	ES	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	32.68 in (83 cm)
Package 1 width	24.21 in (61.5 cm)
Package 1 Length	12.60 in (32 cm)

Offer Sustainability

Green Premium product
☑ REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
€Yes
China RoHS Declaration
Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------