


GBJ25005-GBJ2510


Single-Phase 25.0A Glass Passivated Bridge Rectifier



Features

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Plastic material-UL flammability 94V-0
- This is a Pb – Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

Circuit Diagram



Mechanical Data

- Case: GBJ, Molded plastic
- Terminals: Plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting Position: Any
- Lead Free: For RoHS / Lead Free Version

Maximum Ratings @ $T_A=25^{\circ}\text{C}$ unless otherwise specified

| Type Number | Symbol | GBJ 25005 | GBJ 2501 | GBJ 2502 | GBJ 2504 | GBJ 2506 | GBJ 2508 | GBJ 2510 | Units |
|---|------------------------------------|-----------|----------|----------|----------|----------|----------|----------|-------|
| Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage | V_{RRM} V_{RWM} V_{DC} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| RMS Reverse Voltage | V_{RMS} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V |
| Average forward rectified output current @ $T_A=100^{\circ}\text{C}$ | $I_{(AV)}$ | 25.0 | | | | | | | A |
| Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method) | I_{FSM} | 300 | | | | | | | A |

Electrical Characteristics @ $T_A=25^{\circ}\text{C}$ unless otherwise specified

| Type Number | Symbol | GBJ 25005 | GBJ 2501 | GBJ 2502 | GBJ 2504 | GBJ 2506 | GBJ 2508 | GBJ 2510 | Units |
|---|----------|-----------|----------|----------|-------------|----------|----------|----------|---------------|
| Forward Voltage (per element) @ $I_F = 12.5\text{A}$ @ $I_F = 25\text{A}$ | V_F | | | | 1.0 1.1 | | | | V |
| Peak Reverse Current @ $T_A = 25^{\circ}\text{C}$ At Rated DC Blocking Voltage @ $T_A = 125^{\circ}\text{C}$ | I_{RM} | | | | 10.0 500 | | | | μA |
| Typical Junction Capacitance(per leg) (Note 1) | C_J | | | | 85 | | | | pF |



* Pulse width < 300 μs , duty cycle < 2%



Thermal-Mechanical Specifications:

| Type Number | Symbol | GBJ 25005 | GBJ 2501 | GBJ 2502 | GBJ 2504 | GBJ 2506 | GBJ 2508 | GBJ 2510 | Units |
|---|------------------------------------|-----------|----------|----------|-------------|----------|----------|----------|----------------------|
| Between Junction and Ambient, Without heatsink Between Junction and Case, Without heatsink | $R_{\theta JA}$ $R_{\theta JC}$ | | | | 22 1.0 | | | | $^{\circ}\text{C/W}$ |
| Operating and Storage Temperature Range | T_J, T_{STG} | | | | -55 to +150 | | | | $^{\circ}\text{C}$ |

Note: 1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

Ratings and Characteristics Curves






Ordering Information

| Device | Package | Plating | Shipping |
|-----------------------------|--------------|---------|--------------|
| GBJ25005 THRU GBJ2510 | GBJ(Pb-Free) | Pure Sn | 15pcs / tube |

For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.

Marking Diagram




Where XXXXX is YYWWL

SSG = SSG
YY = Year
WW = Week
L = Lot Number
GBJ25005 = Type Number

Cautions: Molding resin
Epoxy resin UL:94V-0

Mechanical Dimensions GBJ (Inches/Millimeters)





**GBJ25005
THRU
GBJ2510**

**Technical Data
Data Sheet N1754, Rev. A**



DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.