



- **Split design allows side entry** and encirclement of preassembled harnesses, power cords, capillary tubes or other assemblies that have segments larger than the bushing's ID.
- Parts can be assembled into holes that already contain cables or tubing.
- Only fingertip pressure required to snap-lock the bushing into its mounting hole.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Flexible shutters adjust to accommodate and support any shape from .125" (3,2 mm) to a maximum cable/bundle diameter of 1.970" (43,2 mm).
- Absorb vibration, cushion and insulate cables, tubing, hoses or shafts.
- Available in multiple sizes for use in .500" (12,7 mm) to 2.500" (63,5 mm) diameter holes.

## Heyco® Open/Closed Universal Bushings



Mounting Hole Diameter Range: .500" (12,7 mm) to 2.500" (63,5 mm)

MOUNTING HOLE DIAMETER		PART NO. Black	DESCRIPTION	PART DIMENSIONS					
in.	mm.			Maximum Cable/ Bundle Diameter		A Head Diameter		B Overall Height	
				in.	mm.	in.	mm.	in.	mm.
Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)									
.500	12,7	<b>2055SP</b>	OCUB 500	.31	7,6	.56	14,2	.39	9,8
.625	15,9	<b>2077SP</b>	OCUB 625	.44	11,1	.69	17,5		
.750	19,1	<b>2089SP</b>	OCUB 750	.50	12,7	.50	20,3		
.875	22,2	<b>2119SP</b>	OCUB 875	.56	14,3	.92	23,4		
1.000	25,4	<b>2137SP</b>	OCUB 1000	.75	19,1	1.05	26,7	.41	10,3
1.093	27,8	<b>2157SP</b>	OCUB 1093	.81	20,6	1.16	29,5		
1.250	31,8	<b>2196SP</b>	OCUB 1250	.94	23,8	1.44	36,6		
1.375	34,9	<b>2184SP</b>	OCUB 1375	1.00	25,4	1.44	36,6		
1.500	38,1	<b>2213SP</b>	OCUB 1500	1.06	26,9	1.56	39,6		
2.000	50,8	<b>2422SP</b>	OCUB 2000	1.64	41,7	2.12	53,9	.42	10,7

Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)

2.500	63,5	<b>2440SP</b>	OCUB 2.5	1.97	43,2	2.60	66,0	.72	18,3
-------	------	---------------	----------	------	------	------	------	-----	------

Standard color black. Consult Heyco for white and other colors.



Quick  
Specs

Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories, File E15331 Certified by the Canadian Standards Association, File 8919
Flammability Rating	94V-2
Temperature Range	-4°F (-18°C) to 221°F (105°C)