

Han CGM-M M20x1,5 D.10-14mm



| Part number | 19 00 000 5084 |
|--------------------|-------------------------------------|
| Specification | Han CGM-M M20x1,5 D.10-14mm |
| HARTING eCatalogue | https://b2b.harting.com/19000005084 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Accessories |
|--------------------------|------------------------|
| Series of hoods/housings | Han [®] CGM-M |
| Type of accessory | Cable gland |

Technical characteristics

| Tightening torque | ≤10 Nm (depending on the cable and the seal insert used) |
|--|--|
| Wrench size | 24 |
| Limiting temperature | -40 +100 °C |
| Degree of protection acc. to IEC 60529 | IP68 IP69 / IPX9K acc. to ISO 20653 |
| Size | M20 |
| Clamping range | 10 14 mm |
| Width across corners | 26.5 mm |

Material properties

| Material (seal) | NBR |
|--------------------------|--|
| Material (cable glands) | Brass |
| Material (clamping ring) | Polyamide (PA) |
| Surface (accessories) | Nickel plated |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |



Material properties

| REACH Annex XVII substances | No |
|-----------------------------|------|
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |

Specifications and approvals

| Approvals | DNV GL |
|-----------|----------------------------------|
| UL / CSA | UL 514B QCRV.E479780 |
| | CSA-C22.2 No. 18.3 QCRV7.E479780 |

Commercial data

| Packaging size | 10 |
|--------------------------------|--|
| Net weight | 30.9 g |
| Country of origin | Germany |
| European customs tariff number | 84849000 |
| eCl@ss | 27144432 Screwed cable gland (electr.) |