

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter



1162603

<https://www.phoenixcontact.com/us/products/1162603>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VIP VARIOFACE front adapter, with connected system cables for ControlLogix<sup>®</sup> 1756 I/O. Up to 2 x 8 channels can be connected.

## Your advantages

- Individual I/O modules lock to the controller for connection security
- Disconnect lever aids in removal from I/O card
- Marking label can be attached
- Pluggable screw terminals on adapter for power connection

## Commercial data

Item number	1162603
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C423
Product key	CK2311
GTIN	4063151172190
Weight per piece (excluding packing)	440 g
Customs tariff number	85444290
Country of origin	DE

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter



1162603

<https://www.phoenixcontact.com/us/products/1162603>

## Technical data

### Product properties

Product type	Front adapter
Product family	VARIOFACE Professional

### Electrical properties

Max. permissible operating voltage	120 V AC
Max. permissible current	1 A (per path)
	8 A (per group, positive terminals)
	8 A (per group, negative terminals)

Supported controller ALLEN-BRADLEY ControlLogix

Suitable I/O card	1756-OA16
	1756-OB16E

### Connection data

#### Controller level

Connection method	Plug-in connection
Note	Can be plugged onto 20-pos. I/O modules

#### Field level

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	2
Number of positions	14
Pitch	2.54 mm

#### Supply

Connection method	Push-in / plug connection
Stripping length	9 mm
Conductor cross section rigid	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section AWG	26 ... 16

### Dimensions

#### Item dimensions

Width	344.822 mm
Height	47.352 mm
Depth	56.345 mm

#### Cable

Length	2 m
--------	-----

### Cable/line

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter



1162603

<https://www.phoenixcontact.com/us/products/1162603>

## 14X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	14
Shielded	no
Cable type	14X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	14x 0.14 mm <sup>2</sup>
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	6.40 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	55 mm
Smallest bending radius, movable installation	104 mm
Max. bending cycles	5000 (at a radius of ≥ 15x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable) VDE 0842, Part 332-1-2 (raw cable) IEC 60332-3-22 (raw cable) UL VW-1 CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Cable type	Front adapter with splitting cable for two modules

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 60 °C
Ambient temperature (storage/transport)	0 °C ... 80 °C
Altitude	≤ 2000 m (Above sea level)
Permissible humidity (operation)	≤ 95 % (non-condensing)

## Standards and regulations

Standards/regulations	UL 61010-2-201
-----------------------	----------------

## Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also
---------	--

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter



1162603

<https://www.phoenixcontact.com/us/products/1162603>

be met.

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter




1162603

<https://www.phoenixcontact.com/us/products/1162603>

## Drawings

Circuit diagram



1162603

<https://www.phoenixcontact.com/us/products/1162603>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1162603>



**UL Classified**

Approval ID: E238705



**cUL Classified**

Approval ID: E238705



**cUL Recognized**

Approval ID: E196811



**UL Recognized**

Approval ID: E196811

**cULus Classified**

**cULus Recognized**

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter



1162603

<https://www.phoenixcontact.com/us/products/1162603>

## Classifications

### ECLASS

ECLASS-11.0	27242292
ECLASS-12.0	27242292
ECLASS-13.0	27242292

### ETIM

ETIM 9.0	EC002584
----------	----------

1162603

<https://www.phoenixcontact.com/us/products/1162603>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
-------------------------------------	----------------------



# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter

1162603

<https://www.phoenixcontact.com/us/products/1162603>



## Accessories

### VIP-2/SC/FLK14/PLC - Passive module

2315214

<https://www.phoenixcontact.com/us/products/2315214>

VARIOFACE interface module for 8 channels



---

### VIP-2/PT/FLK14/PLC - Passive module

2903801

<https://www.phoenixcontact.com/us/products/2903801>

VARIOFACE interface module, with push-in connection for 8 channels



# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter

1162603

<https://www.phoenixcontact.com/us/products/1162603>



## VIP-2/SC/FLK14/LED/PLC - Passive module

2322249

<https://www.phoenixcontact.com/us/products/2322249>



VARIOFACE interface module, with LED, for 8 channels

---

## VIP-2/PT/FLK14/LED/PLC - Passive module

2904279

<https://www.phoenixcontact.com/us/products/2904279>



VARIOFACE interface module, with push-in connection and light indicator, for 8 channels

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter

1162603

<https://www.phoenixcontact.com/us/products/1162603>



## VIP-2/SC/FLK14/8M/PLC - Passive module

2322281

<https://www.phoenixcontact.com/us/products/2322281>



VARIOFACE interface module, for 8 channels, each with an additional terminal block per signal for a common minus potential

---

## VIP-2/PT/FLK14/8M/PLC - Passive module

2904283

<https://www.phoenixcontact.com/us/products/2904283>



VARIOFACE interface module, with push-in connection, for 8 channels, each with an additional terminal block per signal for a common minus potential

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter




1162603

<https://www.phoenixcontact.com/us/products/1162603>

## FLKM 14/KDS3-MT/PPA/PLC - Passive module

2290423

<https://www.phoenixcontact.com/us/products/2290423>



VARIOFACE interface module, for 8 channels with knife disconnect terminal blocks and test sockets to the peripherals and the system

---

## PLC-V8/FLK14/OUT - System connection

2295554

<https://www.phoenixcontact.com/us/products/2295554>



V8 adapter for 8 x PLC-INTERFACE (6.2 mm), controller: PLC system cabling of output cards, connection 1: IDC/FLK pin strip 1x 14-position, connection 2: Plug-in connection (Can be snapped onto 8x PLC-INTERFACE terminals), connection 3: Screw connection 1x 2-position, number of channels: 8, control logic: plusschaltend

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter

1162603

<https://www.phoenixcontact.com/us/products/1162603>

## PLC-V8L/FLK14/OUT - System connection

2299660

<https://www.phoenixcontact.com/us/products/2299660>



V8 adapter for 8 x PLC-INTERFACE (14 mm), controller: PLC system cabling of output cards, connection 1: IDC/FLK pin strip 1x 14-position, connection 2: Plug-in connection (Can be snapped onto 8x PLC-INTERFACE terminals), connection 3: Screw connection 1x 2-position, number of channels: 8, control logic: plusschaltend

---

## RIF-1-V8/PT/FLK14/OUT - System connection

2905195

<https://www.phoenixcontact.com/us/products/2905195>



V8 adapter for 8 x RIF-1 relay base, controller: PLC system cabling of output cards, connection 1: Push-in connection 4x, connection 2: IDC/FLK pin strip 1x 14-position, connection 3: Plug-in connection, number of channels: 8, control logic: plusschaltend

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter

1162603

<https://www.phoenixcontact.com/us/products/1162603>



## KME - Cable marker carrier

0807083

<https://www.phoenixcontact.com/us/products/0807083>



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 x 8 mm

---

## SF-SL 1,0X5,5-150 - Screwdriver

1212552

<https://www.phoenixcontact.com/us/products/1212552>



Screwdriver, bladed (lasered), size: 1.0 x 5.5 x 150 mm, 2-component grip, with non-slip grip

# VIP-PA-2X14/26/ 2,0M/1756/063 - Front adapter



1162603

<https://www.phoenixcontact.com/us/products/1162603>

## ZBF10:UNBEDRUCKT - Zack Marker strip, flat

0809997

<https://www.phoenixcontact.com/us/products/0809997>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 10 mm, lettering field size: 5.15 x 10 mm, Number of individual labels: 10

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)