

## Specification Sheet

Part Number: 151-02986



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple bracket configurations mount to a variety of surfaces

Releasable to allow for maintenance

Conduit Clamps, Size 25, Mounting Hole 10.6 mm, Offset 50.0 mm, PA66HIRHS, Black, 50/pkg

Article Number

151-02986

Type

CDC25B90OS50M10

Color

Black (BK)

Quantity Per

carton

Product Description

The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters. Choose from arrowhead, fir tree, bundling clip, bracket and dual clamp configurations.

Short Description

Conduit Clamps, Size 25, Mounting Hole 10.6 mm, Offset 50.0 mm, PA66HIRHS, Black, 50/pkg

|                  |                              |
|------------------|------------------------------|
| Global Part Name | CDC25B90OS50M10-PA66HIRHS-BK |
|------------------|------------------------------|

|                     |      |
|---------------------|------|
| Length L (Imperial) | 2.94 |
|---------------------|------|

|                   |      |
|-------------------|------|
| Length L (Metric) | 74.8 |
|-------------------|------|

|         |        |
|---------|--------|
| Variant | Clamps |
|---------|--------|

|                    |     |
|--------------------|-----|
| Width W (Imperial) | 0.9 |
|--------------------|-----|

|                  |    |
|------------------|----|
| Width W (Metric) | 23 |
|------------------|----|

|                                |      |
|--------------------------------|------|
| Bundle Diameter Max (Imperial) | 0.98 |
|--------------------------------|------|

|                              |      |
|------------------------------|------|
| Bundle Diameter Max (Metric) | 25.0 |
|------------------------------|------|

|                     |      |
|---------------------|------|
| Height H (Imperial) | 4.03 |
|---------------------|------|

|                   |       |
|-------------------|-------|
| Height H (Metric) | 102.4 |
|-------------------|-------|

|                             |      |
|-----------------------------|------|
| Inner Diameter D (Imperial) | 1.39 |
|-----------------------------|------|

|                           |      |
|---------------------------|------|
| Inner Diameter D (Metric) | 35.4 |
|---------------------------|------|

|                       |      |
|-----------------------|------|
| Diameter D (Imperial) | 1.06 |
|-----------------------|------|

|                     |      |
|---------------------|------|
| Diameter D (Metric) | 27.0 |
|---------------------|------|

|                             |   |
|-----------------------------|---|
| Nominal Diameter (Imperial) | 1 |
|-----------------------------|---|

|                           |      |
|---------------------------|------|
| Nominal Diameter (Metric) | 25.4 |
|---------------------------|------|

|                                     |                                                                  |
|-------------------------------------|------------------------------------------------------------------|
| Mounting Hole Diameter D (Imperial) | 0.42                                                             |
| Mounting Hole Diameter D (Metric)   | 10.6 mm                                                          |
| Material                            | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut                   | PA66HIRHS                                                        |
| Flammability                        | UL 94 HB                                                         |
| Halogen Free                        | No                                                               |
| UV Resistant (Yes/No)               | No                                                               |
| Operating Temperature               | -40°F to +230°F (-40°C to +110°C)                                |
| Reach Compliant (Article 33)        | Yes                                                              |
| ROHS Compliant                      | Yes                                                              |
| Package Quantity (Imperial)         | 50                                                               |
| Package Quantity (Metric)           | 50                                                               |
| Customs Number                      | 3926909988                                                       |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)