

## **Specification Sheet**

Part Number: 151-03985



Smaller footprint for applications where space is constrained. Can be hand-twisted onto a threaded rod, allowing for quick installation, adjustment or removal.

Clamp interior is designed to guide and center bundles to reduce pinching.

3/8" Threaded Rod Mount Ratchet Clamp, 0.76 - 1.42" Bundle Dia, PA66HIRHSUV, Black, 25/bg

Article Number 151-03985

Type CMRCCTR38

Color Black (BK)

Quantity Per bag

**Product Description** 

The Threaded Rod Mount Ratchet Clamp offers versatility when managing conduit, wires, cables and hoses. Specially designed for locations with space constraints or where offset mounting options are not ideal. Easily twists onto existing threaded rods, eliminating the need for additional hardware. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface.

| Short Description                    | 3/8" Threaded Rod Mount Ratchet Clamp, 0.76 - 1.42" Bundle Dia, PA66HIRHSUV, Black, 25/bg |  |  |
|--------------------------------------|---|--|--|
| Global Part Name                     | CMRCCTR38-PA66HIRHSUV-BK  |  |  |
| Minimum Tensile Strength (Imperial)  | 250   |  |  |
| Minimum Tensile Strength (Metric)    | 1112  |  |  |
| Length L (Imperial)                  | 4.93  |  |  |
| Length L (Metric)                    | 125.22  |  |  |
| Fixation Method                      | 3/8" Threaded Rod   |  |  |
| Width W (Imperial)  Width W (Metric) | 1.38<br>35.1  |  |  |
| Bundle Diameter Min (Imperial)       | 0.76  |  |  |
| Bundle Diameter Min (Metric)         | 19.3  |  |  |
| Bundle Diameter Max (Imperial)       | 1.42  |  |  |
| Bundle Diameter Max (Metric)         | 36.1  |  |  |
| Height H (Imperial)                  | 1.20  |  |  |
| Height H (Metric)                    | 30.48   |  |  |
|                                      |   |  |  |

0.375 "

**Bolt Size** 

Material Polyamide 6.6 high impact modified, heat and UV stabilized

(PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Halogen Free Yes

UV Resistant (Yes/No) Yes

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

UL Listed (US) Yes

Package Quantity (Imperial) 25

Package Quantity (Metric) 25

Customs Number 3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar,

| uction, quality | assurance and delivery is opti | mized to bene   | fit local and global |
|-----------------|--------------------------------|---|----------------------|
|                 |                                |   |                      |
|                 |                                |   |                      |
|                 |                                |   |                      |
|                 |                                |   |                      |
|                 |                                |   |                      |
|                 |                                |   |                      |
| Reserved.       | RoHS/WEEE Compliance           | Disclaimer  | Terms and Conditions |
|                 |                                |   |                      |
|                 |                                |   |                      |
|                 |                                |   |                      |
|                 |                                |   |                      |
|                 |                                |   |                      |
|                 | s Reserved.                    | uction, quality assurance and delivery is opti<br>is in 39 countries, with North American heado |                      |