

## Specification Sheet

Part Number: 156-00049



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole

Edge Clip provides low insertion force and high extraction force ideal for assembly environments

Rotatable Cable Tie and Edge Clip, 6.3" Length, Outside Serrated, PA66HS, Black, 500/bg

Article Number 156-00049

Type CBT30MR

Color Black (BK)

Quantity Per carton

**Product Description**

HellermannTyton's Two-Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place. The clips are available in 90° and 360° models for use with different types of cable tie. On the CBT30MR the bundle runs at the side of the clip and the cable tie is outside serrated to reduce bundle abrasion.

**Short Description**

Rotatable Cable Tie and Edge Clip, 6.3" Length, Outside Serrated, PA66HS, Black, 500/bg

Global Part Name CBT30MR-PA66HS/POM-BK

Minimum Tensile Strength (Imperial) 30.0

Minimum Tensile Strength (Metric) 135

Length L (Imperial) 6.3

Length L (Metric) 160

Fixation Method Edge Clip

Identification Plate Position none

Variant Inside Serrated

Width W (Imperial) 0.14

Width W (Metric) 3.5

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 1.3

Bundle Diameter Max (Metric) 32.0

Cable Tie Head Length (Imperial) 3.5

Height H (Imperial) 0.05

|                                |   |
|--------------------------------|---|
| Height H (Metric)              | 1.2   |
| Cable Tie Width Max (Imperial) | 0.14  |
| Cable Tie Width Max (Metric)   | 3.5   |
| Panel Thickness Min (Imperial) | 0.04  |
| Panel Thickness Max (Imperial) | 0.12  |
| Panel Thickness Min (Metric)   | 1.0   |
| Panel Thickness Max (Metric)   | 2.5   |
| Material                       | Polyacetal (POM) Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut              | PA66HS POM  |
| Material Cable Tie             | Polyamide 6.6 heat stabilized (PA66HS)                  |
| Flammability                   | UL 94 HB  |
| UV Resistant (Yes/No)          | No  |
| Operating Temperature          | -40°F to +194°F (-40°C to +90°C)                        |
| Reach Compliant (Article 33)   | Yes   |
| ROHS Compliant                 | Yes   |

|                             |            |
|-----------------------------|------------|
| Package Quantity (Imperial) | 500        |
| Package Quantity (Metric)   | 500        |
| Customs Number              | 3926909988 |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)