# Pan/Tilt/Zoom HD Color Camera

PTZ-HD30-18-C

- 1080p HD video with 33x optical zoom
- Suitable for harsh weather environments
   & indoor applications
- H.265, H.264,
   MJPEG multistreaming
- Integrated IR illuminators
- 24VDC, 24VAC, or PoE\*



#### Rugged 1080p HD PTZ camera for low light applications

The PTZ-HD30-18-C is a high quality, high-definition color video camera with outstanding low-light performance. It has a 33x motor-driven optical zoom. The PTZ-HD30-18-C can provide multiple streams of high frame rate video.

The camera automatically switches to black and white and removes an IR cut filter to increase sensitivity in low light conditions. The integrated IR LEDs provide quality performance in complete darkness up to 150 meters.

The high speed pan, tilt, and zoom functions can be controlled automatically and precisely from anywhere using the click-to-point and preset view features of IVC's camera management software packages.

The camera is housed in a weatherproof enclosure rated IP66. It requires only a power source and Ethernet connection for installation.



## ▶ specifications

•	
Imager	2 Megapixel 1/2.8" Progressive CMOS
Resolution	1920(H)×1080(V)
Shutter Speed	1~1/100K sec.
Minimum Illumination	Color: 0.001 Lux (F1.5, AGC On) 0 Lux to 150 m with IR ON
F number	F1.5
Focal Length	4.5mm - 148.5mm
Zoom ratio	33x
Iris	Auto and Manual
Day/night	Auto
Focus	Auto and Manual
White Balance	Auto, Manual, ATW
View Angle	56.2° (wide), 2.6 °(tele)
I/O Terminals	2 Inputs; 1 Output
Ethernet	100Base-TX/10BaseT (RJ-45)
Protocols	TCP/IP, HTTP, HTTPS, FTP, SMTP, ONVIF
Compression	M-JPEG, H.265/H.264
Frame Rate	60 FPS
Voltage Required	24 VAC, 24 VDC, Proprietary PoE (110-220 VAC option available)
Power Consumption	48 W max
Weight	11.68lbs
Operating Temperature	-40° C - 65° C
Dimensions	8.9" W x 14.2" H
Mount	Wall Mount Standard
Enclosure Rating	IP66
Certifications	IEC 62368-1 UL 60950-1 FCC Part 15 EN 55032:2015 EN 55024:2010 EN 61000-3-2:2014 EN 61000-3-3-2013

### ▶ features



1080p high-definition broadcast quality images for detailed post-event analysis



30 frames per second for smooth video



Rated IP66 for all weather applications

# ▶ ordering information

PTZ-HD30-18-C

# ►IVC camera management software

#### Point & click camera management & control

Robust, enterprise class software to manage and control your cameras and video from anywhere in the world.



### ▶ accessories

MB-100-5-C Pole Mount Bracket

MB-100-8-C Corner Mount Bracket

MB-100-15-C Junction Box Mount

