


AMP

TE Internal #: 5-530518-1 Socket Contact, Tin, Locking Lance Contact Retention, 16 – 14 AWG Wire Size, 1.25 – 2 mm² Wire Size, 2580 – 4110 CMA Wire Size, Crimp, Copper Alloy

View on TE.com >

Connectors > Contacts > Connector Contacts



Contact Type: Socket Contact Mating Area Plating Material: Tin Wire Contact Termination Area Plating Material: Tin Contact Retention Within Housing: With Contact Retention Type Within Housing: Locking Lance

Features

Contact Features

Wire Contact Termination Area Plating Material Finish	Matte
Contact Mating Area Plating Material Finish	Matte
Contact Type	Socket



Contact Mating Area Plating Material	Tin
Wire Contact Termination Area Plating Material	Tin
Contact Retention Within Housing	With
Contact Base Material	Copper Alloy
Termination Features	
Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable
Mechanical Attachment	
Contact Retention Type Within Housing	Locking Lance
Dimensions	
Compatible Insulation Diameter Range	2.29 – 3.68 mm[.09 – .145 in]
Wire Size	2580 – 4110 CMA
Operation/Application	
Circuit Application	Power & Signal
Packaging Features	

C For support call+1 800 522 6752

5-530518-1

Socket Contact, Tin, Locking Lance Contact Retention, 16 – 14 AWG Wire Size, 1.25 – 2 mm² Wire Size, 2580 – 4110 CMA Wire Size, Crimp, Copper Alloy




Packaging Quantity	500
Packaging Method	Loose Piece
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought



Documents

Product Drawings

C For support call+1 800 522 6752

5-530518-1

Socket Contact, Tin, Locking Lance Contact Retention, 16 – 14 AWG Wire Size, 1.25 – 2 mm² Wire Size, 2580 – 4110 CMA Wire Size, Crimp, Copper Alloy



CONT.HIGH CURRENT L.P.

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-530518-1_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-530518-1_M.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_5-530518-1_M.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English