

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△						△					
△						△					
APPLICABLE STANDARD											
RATING	OPERATING TEMPERATURE RANGE		-55 °C TO 85 °C ⁽¹⁾			STORAGE TEMPERATURE RANGE		-10 °C TO 60 °C ⁽²⁾			
	VOLTAGE		125 V AC			OPERATING HUMIDITY RANGE		40 % TO 80 %			
	CURRENT		0.5 A			STORAGE HUMIDITY RANGE		40 % TO 70 % ⁽²⁾			
SPECIFICATIONS											
ITEM		TEST METHOD				REQUIREMENTS			QT	AT	
CONSTRUCTION											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.			×	×	
MARKING		CONFIRMED VISUALLY.							×	×	
ELECTRICAL CHARACTERISTICS											
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).				45 mΩ MAX.			×		
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV MAX, 1 mA(DC OR 1000Hz)				55 mΩ MAX.			×		
INSULATION RESISTANCE		250 V DC.				100 MΩ MIN.			×		
VOLTAGE PROOF		300 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.			×		
MECHANICAL CHARACTERISTICS											
MECHANICAL OPERATION		500 TIMES INSERTIONS AND EXTRACTIONS.				① CONTACT RESISTANCE: 55 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			×		
VIBRATION		FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.52 mm, AT 2 h FOR 3 DIRECTION.				① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			×		
SHOCK		490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.							×		
ENVIRONMENTAL CHARACTERISTICS											
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.				① CONTACT RESISTANCE: 55 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN.			×		
RAPID CHANGE OF TEMPERATURE		TEMPERATURE-55→+15~+35→+85→+15~+35°C TIME 30 → 10~15 → 30 → 10~15 min UNDER 5 CYCLES.				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			×		
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				① CONTACT RESISTANCE: 55 mΩ MAX. ② NO HEAVY CORROSION.			×		
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38)							×		
RESISTANCE TO SOLDERING HEAT		1) SOLDER BATH:SOLDER TEMPERATURE, 260±5°C FOR IMMERSION,DURATION,10±1s. 2) SOLDERING IRONS : 360°C FOR 5 s.				NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.			×		
SOLDRABILITY		SOLDERED AT SOLDER TEMPERATURE 240±3°C FOR IMMERSION DURATION, 2s.				A NEW UNIFORM COATING OF SOLDER SHALL OVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.			×		
REMARKS											
1)TEMPERATURE RISE INCLUDED WHEN ENERGIZED. 2)THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.						DRAWN I.OKAYAMA 04.06.09	DESIGNED K.NAKAMURA 04.06.09	CHECKED H.Okawa 04.06.09	APPROVED H.Okawa 04.06.09	RELEASED	
Unless otherwise specified, refer to MIL-STD-1344.											
Note QT:Qualification Test AT:Assurance Test ×:Applicable Test											
HRS HIROSE ELECTRIC CO., LTD.						SPECIFICATION SHEET			PART NO. FX2C1-**P-1. 27DSA (71)		
CODE NO.(OLD) CL			DRAWING NO. ELC4 - 083047-21			CODE NO. CL 572			1 1		