


MULTILAYER CERAMIC CHIP CAPACITORS

Automotive grade, high voltage (1,000V and over)

CGA series

CGA6	3225 [EIA 1210]
CGA7	4520 [EIA 1808]
CGA8	4532 [EIA 1812]
CGA9	5750 [EIA 2220]

*Dimensions code: JIS[EIA]



REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using this products.

REMINDERS

1. The products listed in this specification are intended for use in automotive applications under normal operation and usage conditions. The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality requires a more stringent level of safety or reliability, or whose failure, malfunction or defect could cause serious damage to society, person or property.

Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below or for any other use exceeding the range or conditions set forth in this specification sheet. If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in this specification, please contact us.

- | | |
|--|--|
| (1) Aerospace/aviation equipment | (7) Transportation control equipment |
| (2) Transportation equipment (electric trains, ships, etc.) | (8) Public information-processing equipment |
| (3) Medical equipment (excepting Pharmaceutical Affairs Law classification Class1,2) | (9) Military equipment |
| (4) Power-generation control equipment | (10) Electric heating apparatus, burning equipment |
| (5) Atomic energy-related equipment | (11) Disaster prevention/crime prevention equipment |
| (6) Seabed equipment | (12) Safety equipment |
| | (13) Other applications that are not considered general-purpose applications |

When designing your equipment even for general-purpose applications, you are kindly requested to take into consideration securing protection circuit/device or providing backup circuits in your equipment.

In addition, although the products listed in this specification are intended for use in automotive applications as described above, they are not prohibited to use in general electronic equipment, whose performance and/or quality doesn't require a more stringent level of safety or reliability, or whose failure, malfunction or defect could not cause serious damage to society, person or property. Therefore, the description of this caution will be applied, when the products are used in general electronic equipment under a normal operation and usage conditions.

- We may modify products or discontinue production of a product listed in this catalog without prior notification.
- We provide "Delivery Specification" that explain precautions for the specifications and safety of each product listed in this catalog. We strongly recommend that you exchange these delivery specifications with customers that use one of these products.
- If you plan to export a product listed in this catalog, keep in mind that it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in harmony with this law.
- Any reproduction or transferring of the contents of this catalog is prohibited without prior permission from our company.
- We are not responsible for problems that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. We do not grant license of these rights.
- This catalog only applies to products purchased through our company or one of our company's official agencies. This catalog does not apply to products that are purchased through other third parties.

Notice: Effective January 2013, TDK will use a new catalog number which adds product thickness and packaging specification detail. This new catalog number should be referenced on all catalog orders going forward, and is not applicable for OEM part number orders. Please be aware the last five digits of the catalog number will differ from the item description (internal control number) on the product label. Contact your local TDK Sales representative for more information.

(Example)

Catalog issued date	Catalog number	Item description (on delivery label)
Prior to January 2013	C1608C0G1E103J(080AA)	C1608C0G1E103JT000N
January 2013 and later	C1608C0G1E103J080AA	C1608C0G1E103JT000N

CGA series

High voltage (1,000V and over)



Type: CGA6/3225 [EIA 1210], CGA7/4520 [EIA 1808], CGA8/4532 [EIA 1812],
CGA9/5750 [EIA 2220]

SERIES OVERVIEW

High voltage CGA series, automotive grade of TDK's multilayer ceramic chip capacitor, is a product having a high withstanding voltage characteristic. The lineup is voltage rating of 1,000V to 3,000V with capacitance range up to 33nF.


FEATURES

- Voltage rating: 1,000V, 2,000V, 3,000V
- Operating temperature range: -55~+125°C
- C0G type having excellent stable temperature and DC-bias characteristics is also available
- Qualified based on AEC-Q200

APPLICATION

- Decoupling, snubber and resonant circuits of high voltage circuits
- Wireless charging units, DC-DC converter, Inverter

SHAPE & DIMENSIONS




L	Body length
W	Body width
T	Body height
B	Terminal width

Dimensions in mm

Type	L	W	T	B
CGA6	3.20±0.40	2.50±0.30	2.50±0.30	0.20 min.
CGA7	4.50±0.40	2.00±0.20	2.00±0.20	0.20 min.
CGA8	4.50±0.40	3.20±0.40	2.50±0.30	0.20 min.
CGA9	5.70±0.40	5.00±0.40	2.80±0.30	0.20 min.

* Dimensional tolerances are typical values.

RECOMMENDED CONDITIONS



- It is recommended to provide a slit (about 1mm width) in the board under the components to improve washing flux.
- Please make sure to dry detergent up completely before.
- It is recommended to use low activated flux (Chlorine content: less than 0.1wt%) such rosin due to high voltage usage.
- When mounting on an aluminum substrate, it is more likely to be affected by heat stress from the substrate. Please inquire separate specification when mounted on the substrate.

MULTILAYER CERAMIC CHIP CAPACITORS



CATALOG NUMBER CONSTRUCTION

CGA	6	P	1	COG	3A	223	G	250	A	C
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)

(1)Series

(2)Dimensions L x W (mm)

Code	EIA	Length	Width	Terminal width
6	1210	3.20	2.50	0.20 min.
7	1808	4.50	2.00	0.20 min.
8	1812	4.50	3.20	0.20 min.
9	2220	5.70	5.00	0.20 min.

(3)Thickness code

Code	Thickness
F	0.85 mm
G	1.10 mm
K	1.30 mm
L	1.60 mm
M	2.00 mm
N	2.30 mm
P	2.50 mm
Q	2.80 mm

(4)Voltage condition for life test

Symbol	Condition
1	1 x R.V.

(5)Temperature characteristics

Temperature characteristics	Temperature coefficient or capacitance change	Temperature range
COG	0±30 ppm/°C	-55 to +125°C
X7R	±15%	-55 to +125°C

(6)Rated voltage (DC)

Code	Voltage (DC)
3A	1,000V
3D	2,000V
3F	3,000V

(7)Nominal capacitance (pF)

The capacitance is expressed in three digit codes and in units of pico Farads (pF). The first and second digits identify the first and second significant figures of the capacitance. The third digit identifies the multiplier. R designates a decimal point.

(Example) 0R5 = 0.5pF
 101 = 100pF
 225 = 2,200,000pF = 2.2μF

(8)Capacitance tolerance

Code	Tolerance
F	±1pF
G	±2%
J	±5%
K	±10%
M	±20%

(9)Thickness

Code	Thickness
085	0.85 mm
110	1.10 mm
130	1.30 mm
160	1.60 mm
200	2.00 mm
230	2.30 mm
250	2.50 mm
280	2.80 mm

(10)Packaging style

Code	Style
A	178mm reel, 4mm pitch
K	178mm reel, 8mm pitch


















(11)Special reserved code




Code	Description
A,C	TDK internal code

MULTILAYER CERAMIC CHIP CAPACITORS

Capacitance range chart

CGA6/3225 [EIA 1210]














Capacitance		COG
(pF)	Code	3A (1kV)
1,000	102	
1,200	122	
1,500	152	
1,800	182	
2,200	222	
2,700	272	
3,300	332	
3,900	392	
4,700	472	
5,600	562	
6,800	682	
8,200	822	
10,000	103	
12,000	123	
15,000	153	
18,000	183	
22,000	223	






Standard thickness  2.00mm  2.30mm  2.50mm

■ For details such as the catalog numbers, please refer to the capacitance range table on page 7.

Capacitance range chart

CGA7/4520 [EIA 1808]

Capacitance		COG	X7R	
(pF)	Code	3F (3kV)	3D (2kV)	3A (1kV)
10	100			
15	150			
22	220			
33	330			
47	470			
56	560			
68	680			
82	820			
100	101			
470	471			
1,000	102			








Standard thickness  0.85mm  1.10mm  1.30mm  1.60mm  2.00mm

■ For details such as the catalog numbers, please refer to the capacitance range table on page 7.

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use. Please note that the contents may change without any prior notice due to reasons such as upgrading.

Capacitance range chart

CGA8/4532 [EIA 1812]





Capacitance		COG	X7R		
(pF)	Code		3F (3kV)	3D (2kV)	3A (1kV)
100	101				
150	151				
220	221				
330	331				
2,200	222				
4,700	472				
10,000	103				


Standard thickness  1.30mm  1.60mm  2.00mm  2.50mm

■ For details such as the catalog numbers, please refer to the capacitance range table on page 7.

Capacitance range chart

CGA9/5750 [EIA 2220]

Capacitance		COG
(pF)	Code	
10,000	103	
15,000	153	
22,000	223	
33,000	333	

Standard thickness  2.80mm

■ For details such as the catalog numbers, please refer to the capacitance range table on page 7.

MULTILAYER CERAMIC CHIP CAPACITORS



Capacitance range table

Temperature characteristic: COG (-55 to +125°C, 0±30ppm/°C)

Capacitance	Capacitance Width (mm)	Thickness (mm)	Capacitance tolerance	Catalog number	
				Rated voltage Edc: 3kV	Rated voltage Edc: 1kV
10pF	4520	0.85±0.15	±1pF	CGA7F1C0G3F100F085KA	
15pF	4520	1.10±0.20	±10%	CGA7G1C0G3F150K110KA	
22pF	4520	1.10±0.20	±10%	CGA7G1C0G3F220K110KA	
33pF	4520	1.60±0.20	±10%	CGA7L1C0G3F330K160KA	
47pF	4520	1.60±0.20	±10%	CGA7L1C0G3F470K160KA	
68pF	4520	2.00±0.20	±10%	CGA7M1C0G3F680K200KA	
100pF	4520	2.00±0.20	±10%	CGA7M1C0G3F101K200KA	
	4532	1.60±0.20	±10%	CGA8L1C0G3F101K160KA	
150pF	4532	1.60±0.20	±10%	CGA8L1C0G3F151K160KA	
220pF	4532	2.00±0.20	±10%	CGA8M1C0G3F221K200KA	
330pF	4532	2.50±0.30	±10%	CGA8P1C0G3F331K250KA	
1nF	3225	2.00±0.20	±2%	CGA6M1C0G3A102G200AC	
			±5%	CGA6M1C0G3A102J200AC	
1.2nF	3225	2.00±0.20	±2%	CGA6M1C0G3A122G200AC	
			±5%	CGA6M1C0G3A122J200AC	
1.5nF	3225	2.00±0.20	±2%	CGA6M1C0G3A152G200AC	
			±5%	CGA6M1C0G3A152J200AC	
1.8nF	3225	2.00±0.20	±2%	CGA6M1C0G3A182G200AC	
			±5%	CGA6M1C0G3A182J200AC	
2.2nF	3225	2.00±0.20	±2%	CGA6M1C0G3A222G200AC	
			±5%	CGA6M1C0G3A222J200AC	
2.7nF	3225	2.00±0.20	±2%	CGA6M1C0G3A272G200AC	
			±5%	CGA6M1C0G3A272J200AC	
3.3nF	3225	2.00±0.20	±2%	CGA6M1C0G3A332G200AC	
			±5%	CGA6M1C0G3A332J200AC	
3.9nF	3225	2.00±0.20	±2%	CGA6M1C0G3A392G200AC	
			±5%	CGA6M1C0G3A392J200AC	
4.7nF	3225	2.00±0.20	±2%	CGA6M1C0G3A472G200AC	
			±5%	CGA6M1C0G3A472J200AC	
5.6nF	3225	2.00±0.20	±2%	CGA6M1C0G3A562G200AC	
			±5%	CGA6M1C0G3A562J200AC	
6.8nF	3225	2.00±0.20	±2%	CGA6M1C0G3A682G200AC	
			±5%	CGA6M1C0G3A682J200AC	
8.2nF	3225	2.30±0.20	±2%	CGA6N1C0G3A822G230AC	
			±5%	CGA6N1C0G3A822J230AC	
10nF	3225	2.50±0.30	±2%	CGA6P1C0G3A103G250AC	
	5750	2.80±0.30	±5%	CGA9Q1C0G3A103J280KC	
12nF	3225	2.50±0.30	±2%	CGA6P1C0G3A123G250AC	
			±5%	CGA6P1C0G3A123J250AC	
15nF	3225	2.50±0.30	±2%	CGA6P1C0G3A153G250AC	
			±5%	CGA6P1C0G3A153J250AC	
18nF	3225	2.50±0.30	±2%	CGA9Q1C0G3A153J280KC	
			±5%	CGA6P1C0G3A183G250AC	
22nF	3225	2.50±0.30	±2%	CGA6P1C0G3A223G250AC	
			±5%	CGA6P1C0G3A223J250AC	
33nF	5750	2.80±0.30	±5%	CGA9Q1C0G3A223J280KC	
			±5%	CGA9Q1C0G3A333J280KC	

Click the part numbers for details.

Capacitance range table

Temperature characteristic: X7R (-55 to +125°C, ±15%)

Capacitance	Dimensions	Thickness (mm)	Capacitance tolerance	Catalog number	
				Rated voltage Edc: 2kV	Rated voltage Edc: 1kV
470pF	4520	1.30±0.20	±10%	CGA7K1X7R3D471K130KA	CGA7K1X7R3A471K130KA
			±20%	CGA7K1X7R3D471M130KA	CGA7K1X7R3A471M130KA
1nF	4520	1.30±0.20	±10%	CGA7K1X7R3D102K130KA	CGA7K1X7R3A102K130KA
			±20%	CGA7K1X7R3D102M130KA	CGA7K1X7R3A102M130KA
2.2nF	4532	1.30±0.20	±10%	CGA8K1X7R3D222K130KA	
			±20%	CGA8K1X7R3D222M130KA	
4.7nF	4532	1.60±0.20	±10%		CGA8L1X7R3A472K160KA
			±20%		CGA8L1X7R3A472M160KA
10nF	4532	2.00±0.20	±10%		CGA8M1X7R3A103K200KA
			±20%		CGA8M1X7R3A103M200KA

Click the part numbers for details.

⚠ Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.
Please note that the contents may change without any prior notice due to reasons such as upgrading.