



a YAGEO company

CGP7C331MUYDCAWL25

CGP DISC Comm HV, Ceramic, 330 pF, 20%, 4000 VDC, Y5P, 7.5mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

Click here for the 3D model.

Dimensions	
D	6.5mm MAX
Т	6.5mm MAX
S	7.5mm NOM
LL	25mm MIN
F	0.6mm +/-0.1mm
V	2.1mm +/-0.5mm

Packaging Specifications	
Packaging	Bulk
Packaging Quantity	200

General Information		
Series	CGP DISC Comm HV	
Style	Radial Disc	
RoHS	Yes	
Termination	Tin	
Failure Rate	N/A	
AEC-Q200	No	
Halogen Free	Yes	

Specifications	
Capacitance	330 pF
Capacitance Tolerance	20%
Voltage DC	4000 VDC
Temperature Range	-30/+85°C
Temperature Coefficient	Y5P

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.