

CGS | CGS HS TE Internal #: 9-1625963-2 Power Resistor, 5.6K Ω, 10 W, Wire Wound, 2 Termination, ±50 ppm /°C, 5 %, Wirewound Termination, Loose Piece - Box, 1 Resistor, CGS HS

View on TE.com >

Passive Components > Resistors > Chassis Mount Resistors > Power Resistors: Aluminum Housed, HSA



Resistor Type:Power ResistorResistance Class:Up to 1kΩResistance Value:5.6K Ω

Power Rating: 10 W

Element Type: Wire Wound

All Power Resistors: Aluminum Housed, HSA (384)

Features

Product Type Features

Resistor Type

Element Type

Power Resistor

Wire Wound



Configuration Features

Number of Resistors	1				
Electrical Characteristics					
Operating Voltage	160 V				
Resistance Class	Up to 1kΩ				
Resistance Value	5.6Κ Ω				
Power Rating	10 W				
Passive Component Tolerance	5 %				
Termination Features					
Number of Terminations	2				
Chassis Mount Resistor Termination Type	Wirewound				
Mechanical Attachment					
Panel Mount Feature Type	Flange with Mounting Holes				
Dimensions					

HSA55K6J

Power Resistor, 5.6K Ω , 10 W, Wire Wound, 2 Termination, ±50 ppm/°C, 5 %, Wirewound Termination, Loose Piece - Box, 1 Resistor, CGS HS



Product Height	9 mm[.354 in]				
Product Length	31 mm[1.22 in]				
Product Width	17 mm[.669 in]				
Usage Conditions					
Temperature Coefficient	±50 ppm/°C				
Packaging Features					
Packaging Method	Loose Piece - Box				
Product Compliance For compliance documentation, visit the product page on TE.com>					
EU RoHS Directive 2011/65/EU	Compliant				
EU ELV Directive 2000/53/EC	Compliant				
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold				

EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240)

Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per

homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Hand solderable with lead free solder

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

HSA55K6J

Power Resistor, 5.6K Ω , 10 W, Wire Wound, 2 Termination, ±50 ppm/°C, 5 %, Wirewound Termination, Loose Piece - Box, 1 Resistor, CGS HS





Also in the Series | CGS HS



Other Automotive Connector	Plug & Socket Lighting Connector	RJ45 Connectors(1)	Wire-to-Board Connector Assemblies	
Accessories(1)	Accessories(1)		& Housings(1)	

Customers Also Bought





HSA55K6J

Power Resistor, 5.6K Ω , 10 W, Wire Wound, 2 Termination, ±50 ppm/°C, 5 %, Wirewound Termination, Loose Piece - Box, 1 Resistor, CGS HS



Documents

Product Drawings HSA5 5K6 5%

English

CAD Files

Customer View Model ENG_CVM_CVM_9-1625963-2_U.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_9-1625963-2_U.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_9-1625963-2_U.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.