SQBW4022RJFASTON V ACTIVE


CGS | CGS SQ

TE Internal #: 2-1879068-1 Power Resistor, Wire Wound, 40 W, 22 Ω, 5 %, ±300 ppm/°C, Radial-Leaded FASTON, 10.5 x 8 x 18 mm, Loose Piece - Box, 2 Termination, CGS SQ

View on TE.com >



Passive Components > Resistors > Through-Hole Resistors > Wirewound Resistor: Horizontal Mount



Resistor Type: Power Resistor

Element Type: Wire Wound

Power Rating: 40 W

Resistance Class: Up to $1k\Omega$

Resistance Value: 22Ω

All Wirewound Resistor: Horizontal Mount (157)

Features

Product Type Features

Resistor Type

Element Type

Power Resistor

Wire Wound

Configuration Features

Number of Resistors	1
Electrical Characteristics	
Power Rating	40 W
Resistance Class	Up to 1kΩ
Resistance Value	22 Ω
Passive Component Tolerance	5 %
Body Features	
Lead Type	Radial-Leaded FASTON
Termination Features	
Number of Terminations	2
Dimensions	
Passive Component Dimensions	10.5 x 8 x 18 mm
Usage Conditions	

SQBW4022RJFASTON

Power Resistor, Wire Wound, 40 W, 22 Ω , 5 %, ±300 ppm/°C, Radial-Leaded FASTON, 10.5 x 8 x 18 mm, Loose Piece - Box, 2 Termination, CGS SQ




Temperature Coefficient	±300 ppm/°C
Packaging Features	
Packaging Method	Loose Piece - Box
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Also in the Series | CGS SQ

C For support call +1 800 522 6752

SQBW4022RJFASTON

Power Resistor, Wire Wound, 40 W, 22 Ω , 5 %, ±300 ppm/°C, Radial-Leaded FASTON, 10.5 x 8 x 18 mm, Loose Piece - Box, 2 Termination, CGS SQ





Customers Also Bought



TE Part # 282104-1

TE Part # 281934-2

TE Part # 114017-ZZ

AMP SUPERSEAL 1.5MM, CONNECTOR HOUSING SINGLE WIRE SEAL

SEALING PLUG, SIZE 12/16, WHT

Documents

Product Drawings SQB40 22R 5% (WIRE) 6.35MM FASTON

English

Datasheets & Catalog Pages 4-1773460-6_RESISTIVE_SOLUTIONS_RAIL

English

1309350_PASSIVE_COMPONENT

English

8-1773459-4_POWER_FILTERING_AND_RESISTIVE_SOLUTIONS_FOR_ELEVATORS_AND_ESCALATORS

English