
RLC73PV2ER02FTD V ACTIVE

CGS | CGS RLC73

TE Internal #: 2176589-8 Current Sensing Resistor, Thick Film, 1210, .75 W, .02 $\Omega,$ 1 %, ±600 ppm/°C, Solder, 2 Termination, Height .022 in [.55 mm], CGS RLC73 View on TE.com >

Passive Components > Resistors > Surface Mount Resistors



Resistor Type: Current Sensing Resistor

Element Type: Thick Film

Package Size Code: 1210

Power Rating: .75 W

Resistance Value: $.02 \Omega$

Features

Product Type Features



Resistor Type	Current Sensing Resistor			
Element Type	Thick Film			
Package Size Code	1210			
Configuration Features				
Number of Resistors	1			
Electrical Characteristics				
Power Rating	.75 W			
Resistance Value	.02 Ω			
Resistance Class	Up to 1kΩ			
Passive Component Tolerance	1 %			
Termination Features				
Surface Mount Resistor Termination Type	Solder			
Number of Terminations	2			
Dimensions				

C For support call +1 800 522 6752

RLC73PV2ER02FTD

Current Sensing Resistor, Thick Film, 1210, .75 W, .02 Ω , 1 %, ±600 ppm/°C, Solder, 2 Termination, Height .022 in [.55 mm], CGS RLC73



Product Height	.55 mm[.022 in]	
Product Length	3.1 mm[.122 in]	
Product Width	2.6 mm[.102 in]	
Usage Conditions		
Operating Temperature Range	-55 - 155 °C	
Temperature Coefficient	±600 ppm/°C	
Packaging Features		
Packaging Method	Taped & Reeled	
Product Compliance For compliance documentation, visit the product page on TE.com>		
•	Compliant	
For compliance documentation, visit the product page on TE.com>	Compliant Compliant	
For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU		

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Reflow solder capable to 260°C

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles'(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts


RLC73PV2ER02FTD

Current Sensing Resistor, Thick Film, 1210, .75 W, .02 Ω , 1 %, ±600 ppm/°C, Solder, 2 Termination, Height .022 in [.55 mm], CGS RLC73





Also in the Series | CGS RLC73



Customers Also Bought



			= TE
TE Part # 825433-8	TE Part # 292304-1	TE Part # 1879215-1	TE Part # 1759547-1
MOD 2 PINHDR 1X8 P.	STD USB TYPE B, R/A, T/H	CPF 0402 4K02 0.1% 25PPM 1K RL	mSATA/mini PCI-E 7H G/F



Documents

Product Drawings RLC73PV 2E R02 1% 5K RL

English

CAD Files

Customer View Model ENG_CVM_CVM_2176589-8_BA.3d_igs.zip

RLC73PV2ER02FTD

Current Sensing Resistor, Thick Film, 1210, .75 W, .02 Ω , 1 %, ±600 ppm/°C, Solder, 2 Termination, Height .022 in [.55 mm], CGS RLC73



English

Customer View Model ENG_CVM_CVM_2176589-8_BA.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_2176589-8_BA.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages SMD Low Ohmic - Current Sense Resistors - Type RLC73 Series

English