# LH36300

Circuit breaker, LH, I-Line mount, 300A, 3 pole, 25kA, 600VAC, thermal magnetic





#### Main

Main	
Product or Component Type	Circuit breaker
Trip Unit Technology	Thermal-magnetic

Complementary

Line Rated Current	300 A	
Number of Poles	3P	
Breaking capacity code	Н	
Mounting Mode	I-Line	
Magnetic Hold Current	1500 A	
Magnetic Tripping Current	3000 A	
Electrical connection	Lugs, load I-Line connection, line	
Terminal identifier	AL400LA	
Height	12.5 in (317.50 mm)	
Width	6 in (152.40 mm)	
Depth	4 in (101.60 mm)	
Circuit breaker application	HACR rated	

#### Environment

Certifications	UL Listed[RETURN]CSA

### Ordering and shipping details

Category	US10DE201040	
Discount Schedule	0DE2	
GTIN	785901339410	
Returnability	Yes	
Country of origin	IE	

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	9.29 in (23.6 cm)	
Package 1 Width	11.61 in (29.5 cm)	
Package 1 Length	17.28 in (43.9 cm)	
Package 1 Weight	18.45 lb(US) (8.37 kg)	

## Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

18 months