# Product data sheet Characteristics

## QJA32125

Circuit breaker, PowerPacT Q, 125A, 3 pole, 240VAC, 100kA, I-Line, thermal magnetic, 80%, ABC





#### Main

*********	
Range	PowerPact
Product name	PowerPact Q
Product or Component Type	Circuit breaker
Device Application	Distribution

#### Complementary

Line Rated Current	125 A
Number of Poles	3P
Control Type	Operating handle
Breaking capacity code	J
Breaking capacity	100 kA 120/208 V AC 50/60 Hz UL
[Ue] rated operational voltage	240 V AC 50/60 Hz UL
Network Frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV UL
Trip unit technology	Thermal-magnetic
Magnetic tripping current	2400 A
Magnetic hold current	1200 A
Continuous current rating	80 %
Utilisation category	Category A
Mechanical durability	1000 Cycles loaded 5000 cycles no load
Local signalling	1 trip indicator green)
Mounting mode	I-Line bracket)
Mounting Support	Bracket
Electrical connection	I-Line connection, line Lugs, load
Mounting height	4.5 in (114.30 mm)
Tightening torque	247.82 lbf.in (28 N.m) 0.040.23 in² (25150 mm²) (AWG 4300 kcmil)
Power wire stripping length	0.87 in (22 mm)
Height	6.47 in (164.34 mm)
Width	4.5 in (114.30 mm)
Depth	3.93 in (99.82 mm)
Phase connection	ABC

#### Environment

Standards	UL CSA NEMA NOM-003-SCFI-2000
Product certifications	UL[RETURN]CSA[RETURN]NOM
Ambient Air Temperature for Operation	104158 °F (4070 °C)

### Ordering and shipping details

Category	US10DE201023
Discount Schedule	0DE2
GTIN	785901877608
Returnability	Yes
Country of origin	US

#### **Packing Units**

3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.20 in (15.748 cm)	
Package 1 Width	7.80 in (19.812 cm)	
Package 1 Length	12.20 in (30.988 cm)	
Package 1 Weight	6.65 lb(US) (3.015 kg)	

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free product

#### Contractual warranty

Warranty	18 months
----------	-----------