QOU225H5283

Mini circuit breaker, QOU, 25A, 2 pole, 240 VAC, 10kA, ring terminal



Main	
Product or Component Type	Miniature circuit-breaker
Range of Product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR rated

Complementary

Electrical connection Ring tongue, line side Ring tongue, load side [Ue] rated operational voltage AWG gauge AWG 14AWG 2 aluminium/copper Height 4.05 in (102.87 mm) Width 1.5 in (38.10 mm) Depth 2.95 in (74.93 mm)	
AWG gauge AWG 14AWG 2 aluminium/copper Height 4.05 in (102.87 mm) Width 1.5 in (38.10 mm)	
Height 4.05 in (102.87 mm) Width 1.5 in (38.10 mm)	
Width 1.5 in (38.10 mm)	
Depth 2 95 in (74 93 mm)	
2.00 (*)	
Tightening torque 45 lbf.in (5.08 N.m) (AWG 14AWG 2)	

Environment

2.1711 of the first of the firs	
Product Certifications	CSA[RETURN]IEC[RETURN]UL Listed

Ordering and shipping details

Category	US10DE200900
Discount Schedule	0DE2
GTIN	785901939986
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.10 in (5.334 cm)	
Package 1 Width	3.60 in (9.144 cm)	
Package 1 Length	5.90 in (14.986 cm)	
Package 1 Weight	16.00 oz (453.592 g)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Halogen content performance	Halogen free product

Contractual warranty

- Contraction from the contraction of the contracti	
Warranty	18 months