W51-A151A1-5 - ACTIVE

TE Internal #: 1-1423673-5 Circuit Breakers, Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 5A Current Rating, 1 Pole

View on TE.com >



Relays & Contactors > Circuit Breakers



Circuit Breaker Type: Thermal

Circuit Function: Trip-Free - Switchable

Illuminated: Without

Actuator Color: Black

Operating Voltage: 125 VAC

Features

Product Type Features

Circuit Breaker Style	Angular Button
Illumination Type	No Light
Actuator Type	Rocker
Terminal Configuration	6.35 [.25] Straight Quick Connect Tab

Circuit Breaker Type	Thermal				
Illuminated	Without				
Configuration Features					
Panel Cutout Size	28.5 x 13.5 mm[1.122 x .531 in]				
Circuit Function	Trip-Free - Switchable				
Number of Poles	1				
Electrical Characteristics					
Operating Voltage	50 VDC				
Current Rating	5 A				
Current Rating Interrupt Capacity	5 A 1000A @ 250VAC/50VDC				
Interrupt Capacity					
Interrupt Capacity Body Features	1000A @ 250VAC/50VDC				
Interrupt Capacity Body Features Actuator Color	1000A @ 250VAC/50VDC				

W51-A151A1-5

Circuit Breakers, Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 5A Current Rating, 1 Pole



Mechanical Attachment

Mounting Options

Dimensions

Panel Thickness (Recommended)

Identification Marking

Stamped Marking Type

Snaps Into 1.122 x .531 (28.5 x 13.5) Panel Cutout

.75 – 3 mm[.03 – .118 in]

RESET/OFF Printed

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

EU REACH Regulation (EC) No. 1907/2006

Compliant with Exemptions Not Compliant Restricted Materials Above Threshold Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024

(240)

SVHC > Threshold:

Cd (1.55% in Component Part)

Article Safe Usage Statements:

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

W51-A151A1-5

Circuit Breakers, Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 5A Current Rating, 1 Pole





Customers Also Bought



CRGP 1206 820R 1%	SMA R/A PCB Skt GZD	Dir,Mini,Fixed,NF 2400-2485MHz,	RLC/3PD 2B R316 1% 5K RL
		11dBi,BW6	

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1423673-5_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1423673-5_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1423673-5_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

W51 Rocker-Actuated Thermal Circuit Breaker/Power Switch With Optional Indicator Lamp

English

W51-A151A1-5

Circuit Breakers, Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 5A Current Rating, 1 Pole



Agency Approvals CCC Certificate

English