# 

#### Potter & Brumfield W54

TE Internal #: 5-1423674-2 Circuit Breakers, Thermal, Series Trip, White, Operating Voltage 250 VAC, Operating Voltage 50 VDC, 15A Current Rating, 1 Pole, Potter & Brumfield W54

View on TE.com >

Relays & Contactors > Circuit Breakers



### Circuit Breaker Type: Thermal

Circuit Function: Series Trip

Illuminated: Without

Actuator Color: White

Operating Voltage: 250 VAC

# Features

# **Product Type Features**

Illumination Type	No Light
Actuator Type	Push to Reset
Circuit Breaker Type	Thermal



Illuminated		luminated
-------------	--	-----------

**Configuration Features** 

### Without

Panel Cutout Size	11.2 x 10.01 mm[.441 x .394 in]
Circuit Function	Series Trip
Number of Poles	1
Electrical Characteristics	
Operating Voltage	50 VDC
Current Rating	15 A
Interrupt Capacity	1000A @ 250VAC/50VDC
Body Features	
Actuator Color	White
Contact Features	
Trip Time at 200%	5 - 30 seconds
Termination Features	
Terminal Configuration	6.35 [.25] Straight Quick Connect Tab

**C** For support call +1 800 522 6752

06/22/2024 10:38PM |Page 1

# W54-XA1A99C10-15

Circuit Breakers, Thermal, Series Trip, White, Operating Voltage 250 VAC, Operating Voltage 50 VDC, 15A Current Rating, 1 Pole, Potter & Brumfield W54



#### **Mechanical Attachment**

Mounting Hardware Packaging	No Mounting Hardware
Mounting Bushing	9.8 x 12.6mm Long, Metal
Mounting Options	None

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUN 2020 (209) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**




## W54-XA1A99C10-15

Circuit Breakers, Thermal, Series Trip, White, Operating Voltage 250 VAC, Operating Voltage 50 VDC, 15A Current Rating, 1 Pole, Potter & Brumfield W54



# Also in the Series | Potter & Brumfield W54



# Customers Also Bought



# Documents

CAD Files 3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_5-1423674-2\_C.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_5-1423674-2\_C.3d\_igs.zip

English

Customer View Model

```
ENG_CVM_CVM_5-1423674-2_C.3d_stp.zip
```

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages W54 Push To Reset Only Thermal Circuit Breaker

English

Agency Approvals CCC Certificate

English