W58-XC1A4A-16 ✓ ACTIVE

Potter & Brumfield | Potter & Brumfield W58

TE Internal #: 1423695-4

Circuit Breakers, Thermal, Series Trip, White, Operating Voltage 250 VAC, Operating Voltage 50 VDC, 16A Current Rating, 1 Pole,

Potter & Brumfield W58

View on TE.com >



Relays & Contactors > Circuit Breakers



Circuit Breaker Type: Thermal
Circuit Function: Series Trip

Illuminated: Without
Actuator Color: White

Operating Voltage: 250 VAC

Features

Product Type Features

Illumination Type	No Light
Actuator Type	Push to Reset
Circuit Breaker Type	Thermal
Illuminated	Without

Configuration Features

	.4445 (Diameter) in
Circuit Function	Series Trip
Number of Poles	1

Electrical Characteristics

Operating Voltage	50 VDC
Current Rating	16 A
Interrupt Capacity	2000A @ 50VDC or 1000A @ 250VAC

Body Features

Actuator Color	White

Contact Features

Termination Features

Terminal Configuration	6.35 [.25] Straight Quick Connect Tab



Mechanical Attachment	
Mounting Hardware Packaging	Assembled to Bushing
Mounting Bushing	7/16 x .5 [12.7mm] Long
Mounting Options	Knurled Nut/Hex Nut
Identification Marking	
Stamped Marking Type	Black Rate Marking

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Cadmium oxide (7.95% in Contact) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts





TE Part # 1393160-1 55-010A=NUT,.438-28,KNURL,.625 TE Part # 1393160-3 88-021B=WASHER,LOCK,SPRSTL,.44

Also in the Series | Potter & Brumfield W58



Customers Also Bought

















Documents

CAD Files
3D PDF

3D

Customer View Model ENG_CVM_CVM_1423695-4_J.2d_dxf.zip

English



Customer View Model

ENG_CVM_CVM_1423695-4_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1423695-4_J.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use

Datasheets & Catalog Pages

W58 Push To Reset Only Thermal Circuit Breaker

English

Flyer - UL1500 Ignition Protected Circuit Breakers

English

Agency Approvals

UL

English