10287

Multi9 - comb busbar - 3L - 18 mm pitch - 12 modules - 100A



Main	
Range	Multi9
Product or Component Type	Comb busbar
Mounting Mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	3L
Length in 18 mm modules	12

	Com	olementar	٧
--	-----	-----------	---

Number of ways	4 ways 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	0.71 in (18 mm)
Connector type	tooth
Distance between way	2.13 in (54 mm)
Marking	L1 L2 L3
Insulation	Insulated
Device presentation	Uncuttable
[le] rated operational current	100 A 104 °F (40 °C)
[Ue] rated operational voltage	277 V AC Ph/N 480 V AC Ph/Ph
[Ui] rated insulation voltage	690 V AC
[Uimp] rated impulse withstand voltage	12 kV
Mounting location	Top tunnel type terminals
9 mm pitches	24
Width	8.50 in (216 mm)
Color	Light gray RAL 7035)
Range compatibility	Multi9 Multi9 C60SP

Environment

Standards	IEC 60947-2 GB 14048.2 UL 1077	
Fire resistance	1760 °F (960 °C) 30 s)	

Ordering and shipping details

Category	US10DE200908	
Discount Schedule	0DE2	
GTIN	3303430102878	
Returnability	Yes	
Country of origin	DE	

Packing Units

5	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.51 in (1.3 cm)
Package 1 Width	2.17 in (5.5 cm)
Package 1 Length	8.66 in (22.0 cm)
Package 1 Weight	3.81 oz (108.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	72
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	17.86 lb(US) (8.102 kg)

Offer Sustainability

Circularity Profile	No need of specific recycling operations
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration
Mercury free	Yes
Toxic heavy metal free	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
REACh free of SVHC	Yes
REACh Regulation	REACh Declaration

Contractual warranty

Warranty	18 months
----------	-----------