A9E18038

Acti9 iPB 1NO single push button grey - indicator light green 12-48Vac/dc





Main Range of product Acti9 Product name Acti9 iPB Product or Component Type Device short name iPB Standards IEC 60669-1 IEC 60947-5-1

Complementary

- Compression of the contract	
Contacts type and composition	1 NO
[le] rated operational current	20 A
[Ue] rated operational voltage	250 V AC
Control type	1 push-button Gray
Local signalling	LED indicator green, 100000 h 0.3 W)
Signalling circuit voltage	AC 1248 V 50/60 Hz DC 1248 V
Mounting Mode	Fixed
Mounting Support	35 mm symmetrical DIN rail
Comb busbar and distribution block compatibility	Upside Clario Upside Librio Upside ProDis
9 mm pitches	2
Height	3.23 in (82 mm)
Width	0.71 in (18 mm)
Depth	2.81 in (71.5 mm)
Color	White
Electrical durability	AC-22 30000 cycles AC 50/60 Hz
Connections - terminals	Staggered tunnel terminal1 0.00 in² (0.5 mm²) rigid Staggered tunnel terminal1 0.00 in² (0.5 mm²) flexible Staggered tunnel terminal1 0.00 in² (0.5 mm²) flexible with ferrule Staggered tunnel terminal2 0.00 in² (2.5 mm²) rigid Staggered tunnel terminal2 0.00 in² (2.5 mm²) flexible Staggered tunnel terminal2 0.00 in² (2.5 mm²) flexible with ferrule
Wire stripping length	0.35 in (9 mm)
Tightening torque	8.85 lbf.in (1 N.m)

Environment

Tropicalisation	2
Relative humidity	95 % 131 °F (55 °C)
Ambient Air Temperature for Operation	-31158 °F (-3570 °C)
Ambient Air Temperature for Storage	-40176 °F (-4080 °C)

Ordering and shipping details

Category	US10DE200908	
Discount Schedule	0DE2	
GTIN	3606480088308	
Returnability	Yes	
Country of origin	BE	

Packing Units

PCE
1
2.60 in (6.6 cm)
0.71 in (1.8 cm)
3.23 in (8.2 cm)
1.62 oz (46 g)
BB1
12
3.07 in (7.8 cm)
3.86 in (9.8 cm)
9.17 in (23.3 cm)
21.34 oz (605 g)
S03
108
11.81 in (30 cm)
11.81 in (30 cm)
15.75 in (40 cm)
13.10 lb(US) (5.942 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free plastic parts & cables product

Contractual warranty

Warranty	18 months	