Product data sheet Characteristics

A9S60120

Acti9 - iSW switch - 1 pole - 20 A - 250V





Main

Range Acti9 Product name Acti9 iSW Product or Component Type Device short name iSW Device Application Control Poles description 1P Utilisation category AC-22A Suitability for isolation Yes		
Product or Component Type Device short name iSW Device Application Control Poles description 1P Utilisation category AC-22A	Range	Acti9
Type Device short name iSW Device Application Control Poles description 1P Utilisation category AC-22A	Product name	Acti9 iSW
Device Application Control Poles description 1P Utilisation category AC-22A	•	Switch disconnector
Poles description 1P Utilisation category AC-22A	Device short name	iSW
Utilisation category AC-22A	Device Application	Control
	Poles description	1P
Suitability for isolation Yes	Utilisation category	AC-22A
	Suitability for isolation	Yes

Complementary

[le] rated operational current	20 A 250 V AC 50/60 Hz	
[Ue] rated operational voltage	250 V AC 50/60 Hz	
[Ui] rated insulation voltage	250 V AC 50/60 Hz EN/IEC 60669-2-4	
[Uimp] rated impulse withstand voltage	4 kV	
Control Type	Toggle	
Local signalling	ON/OFF indication	
Contact position indicator	Yes	
Mounting Mode	Fixed	
Mounting Support	DIN rail	
9 mm pitches	2	
Height	3.03 in (77 mm)	
Width	0.71 in (18 mm)	
Depth	2.76 in (70 mm)	
Color	Gray	
Mechanical durability	300000 cycles	
Electrical durability	30000 cycles	
Connections - terminals	Tunnel type terminals - 10 mm² - rigid Tunnel type terminals - 10 mm² - flexible Tunnel type terminals - 10 mm² - flexible with ferrule	
Wire stripping length	0.35 in (9 mm)	
Tightening torque	10.62 lbf.in (1.2 N.m)	

Environment

Standards	EN/IEC 60669-2-4
IP degree of protection	IP4
Pollution degree	2
Tropicalisation	2
Relative humidity	95 % 131 °F (55 °C)
Ambient Air Temperature for Operation	-4122 °F (-2050 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)

Ordering and shipping details

Category	US10DE200908	
Discount Schedule	0DE2	
GTIN	3606480088674	
Returnability	No	
Country of origin	BE	

Packing Units

1 doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	2.28 in (5.8 cm)
Package 1 Length	2.68 in (6.8 cm)
Package 1 Weight	1.83 oz (52.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	3.46 in (8.8 cm)
Package 2 Width	3.70 in (9.4 cm)
Package 2 Length	8.74 in (22.2 cm)
Package 2 Weight	23.84 oz (676.0 g)
Unit Type of Package 3	S03
Number of Units in Package 3	144
Package 3 Height	11.81 in (30.0 cm)
Package 3 Width	11.81 in (30.0 cm)
Package 3 Length	15.75 in (40.0 cm)
Package 3 Weight	18.86 lb(US) (8.553 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

	·
Warranty	18 months