## Product data sheet Characteristics

### **GVAS207**

# Shunt release (MX), TeSys Deca, 200V AC 50Hz





#### Main

Range	TeSys TeSys Deca
Product or Component Type	Shunt trip release
Device short name	GVAS

#### Complementary

Complementary	
Range compatibility	TeSys GV2ME
	TeSys GV2LE
	TeSys GV2L
	TeSys GV2P TeSys GV3L
	TeSys GV3P
	TeSys Deca
[Uc] control circuit voltage	200 V AC 50 Hz
[OU] Control circuit voltage	200220 V AC 60 Hz
Control circuit voltage limits	0.71.1 Un
[Ui] rated insulation voltage	690 V AC IEC 60947-1
	600 V AC UL 60947-4-1
	600 V AC CSA C22.2 No 60947-4-1
Threshold tripping voltage	0.750.2 Un
Inrush power in VA	14 VA AC
Inrush power in W	10.5 W
Hold-in Power Consumption in VA	5 VA AC
Hold-in power consumption in W	1.6 W
Operating time	1015 ms IEC 60947-1
On-load factor	100 %
Connections - terminals	Screw clamp terminals 1 0.000.00 in² (12.5 mm²)solid
	Screw clamp terminals 2 0.000.00 in² (12.5 mm²)solid
	Screw clamp terminals 1 0.000.00 in <sup>2</sup> (0.752.5 mm <sup>2</sup> )flexible without cable
	end Screw clamp terminals 2 0.000.00 in² (0.752.5 mm²)flexible without cable
	end
	Screw clamp terminals 1 0.000.00 in² (0.751.5 mm²)flexible with cable end
	Screw clamp terminals 2 0.000.00 in <sup>2</sup> (0.751.5 mm <sup>2</sup> )flexible with cable end
Tightening torque	< 1.4 N.m screw clamp terminals
Mechanical durability	10000 Cycles with GV3P and GV3L
• • • • • •	30000 cycles with GV2ME and GV2P
Quantity per Set	Set of 10
Height	3.50 in (89 mm)
Width	0.71 in (18 mm)
Depth	2.60 in (66 mm)
Net Weight	0.23 lb(US) (0.105 kg)
Color	Dark grey

### Ordering and shipping details

Category	US10I1122367	
Discount Schedule	0111	
GTIN	3389110343717	
Returnability	No	
Country of origin	CZ	

#### Packing Units

1 doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.38 in (3.500 cm)
Package 1 Width	3.35 in (8.500 cm)
Package 1 Length	3.74 in (9.500 cm)
Package 1 Weight	3.95 oz (112.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	42
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	10.91 lb(US) (4.948 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	672
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	31.50 in (80.000 cm)
Package 3 Length	23.62 in (60.000 cm)
Package 3 Weight	192.17 lb(US) (87.168 kg)

#### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant <sup>☑</sup> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

#### Contractual warranty

Warranty	18 months

GVAS\*\*\*

