



## Main

Product or Component Type	Auxiliary contact
Breaking capacity code	LA Q4 LH

## Complementary

Rated voltage	125...250 V AC 30 V DC
Contacts type and composition	1 NO + 1 NC
Marking	A B
Tightening torque	115.06 Lbf.In (13 N.m) 0.07...0.47 in <sup>2</sup> (42...304 mm <sup>2</sup> ) (AWG 1...600 kcmil) 115.06 Lbf.In (13 N.m) 0.07...0.20 in <sup>2</sup> (42...127 mm <sup>2</sup> ) (AWG 1...250 kcmil) 371.73 lbf.in (42 N.m)

## Environment

Product Certifications	CSA[RETURN]UL Listed
------------------------	----------------------

## Ordering and shipping details

Category	US10DE200985
Discount Schedule	0DE2
GTIN	785901005476
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.30 in (10.922 cm)
Package 1 Width	3.90 in (9.906 cm)
Package 1 Length	8.90 in (22.606 cm)
Package 1 Weight	8.32 oz (235.868 g)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------