



### Main

Range of Product	Square D
Product	Terminal kit
Provided equipment	Lug 1 Screw 2

### Complementary

Device Application	Neutral bar
Current Rating	100 A
Short-circuit withstand	22 kA
Wire Gauge	AWG 4...AWG 2/0 aluminium/copper AWG 14...AWG 6 aluminium/copper
Tightening torque	119.48 Lbf.in (13.5 N.m) 0.03...0.10 in <sup>2</sup> (21.2...67.4 mm <sup>2</sup> ) (AWG 4...AWG 2/0) 30.09 lbf.in (3.4 N.m) 0.00...0.02 in <sup>2</sup> (2.1...13.3 mm <sup>2</sup> ) (AWG 14...AWG 6)

### Ordering and shipping details

Category	US1DE3A00102
Discount Schedule	DE3A
GTIN	785901882831
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.53 in (36.9 cm)
Package 1 Width	0.39 in (1 cm)
Package 1 Length	9.53 in (24.2 cm)
Package 1 Weight	0.02 oz (0.5 g)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes

Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations