# Q0124L200PG

Load center, QO, 1 phase, 24 spaces, 36 circuits, 200A convertible main breaker, PoN, NEMA1, gnd bar, UL





#### Main

QO
Load Center
Grounding bar

#### Complementary

o o in promontary		
Tightening Torque	Cover 20 lb.in	
PoN Convertible Mains (lugs)	PoN Convertible Mains (lugs)	
Rated Current	200 A	
Number of Spaces	24	
Max Short Circuit Current Rating	65 kA	
Maximum Number of Single Pole Circuits	36	
Maximum Number of Tandem Breakers	12	
Number of Phases	1 phase	
Ground Bar	Grounding bar included (not installed)	
Box Number	9	
Height	29.84 in (758 mm)	
Width	14.25 in (362 mm)	
Depth	3.74 in (95 mm)	
Net Weight	25.99 lb(US) (11.790 kg)	

#### Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

#### Ordering and shipping details

Category	US1DE3A10003
Discount Schedule	DE3A
GTIN	785901085898
Returnability	Yes
Country of origin	US
Country of origin	

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.84 in (75.8 cm)
Package 1 Width	14.25 in (36.2 cm)
Package 1 Length	3.74 in (9.5 cm)
Package 1 Weight	16.48 lb(US) (7.475 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations