QO2L30SC

Load center, QO, 1 phase, 2 spaces, 2 circuits, 30A fixed main lugs, NEMA1, surface cover, CSA





Main

Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Surface cover

Complementary

1	
Tightening Torque	Main lugs 35 lb.in, AWG 12AWG10, aluminium/copper
PoN Convertible Mains (lugs)	Fixed Mains (lugs)
Rated Current	30 A
Number of Spaces	2
Max Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	2
Maximum Number of Tandem Breakers	0
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 12AWG 10 aluminium AWG 14AWG 10 copper
Ground Bar	Grounding bar (ordered separately)
Electrical Connection	Lugs
Wiring Configuration	3-wire
Busbar Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Surface Finish	Baked enamel Gray
Box Number	2
Height	6.57 in (167 mm)
Width	3.70 in (94 mm)
Depth	2.95 in (75 mm)

Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	CSA[RETURN]UL Listed

Ordering and shipping details

Category	US1DE3A00156	
Discount Schedule	DE3A	
GTIN	785901207726	
Returnability	Yes	
Country of origin	MX	

Packing Units

3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.02 in (10.2 cm)	
Package 1 Width	4.29 in (10.9 cm)	
Package 1 Length	7.80 in (19.8 cm)	
Package 1 Weight	33.12 oz (938.9 g)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months