QO816L100DSCU

Load center, QO, 1 phase, 8 spaces, 16 circuits, 100A fixed main lugs, NEMA1, door surface cover, Cu bus, UL





Main

TVI CALL	
Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Surface cover with door
Oover Type	Odridoc cover with door

Complementary

Tightening Torque	Main lugs 50 lb.in, AWG 8, aluminium/copper Main lugs 50 lb.in, AWG 6AWG 1/0, aluminium/copper
PoN Convertible Mains (lugs)	Fixed Mains (lugs)
Rated Current	100 A
Number of Spaces	8
Max Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	16
Maximum Number of Tandem Breakers	8
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 8AWG 1 aluminium/copper
Ground Bar	Grounding bar (ordered separately)
Electrical Connection	Lugs
Wiring Configuration	3-wire
Busbar Material	Tin plated copper: busbar
Enclosure Material	Welded sheet steel
Surface Finish	Baked enamel Gray
Box Number	4
Height	12.56 in (319 mm)
Width	8.74 in (222 mm)
Depth	3.74 in (95 mm)
Net Weight	8.60 lb(US) (3.900 kg)

Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	US1DE3A00101
Discount Schedule	DE3A
GTIN	785901626398
Returnability	Yes
Country of origin	US

Packing Units

3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.41 in (11.2 cm)	
Package 1 Width	10.71 in (27.2 cm)	
Package 1 Length	14.29 in (36.3 cm)	
Package 1 Weight	8.49 lb(US) (3.85 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months	