



Main

Marketing Trade Name	QO
Product Type	Mounting base

Complementary

Tightening Torque	Main lugs 50 lb.in, AWG 3...AWG 2, aluminium/copper
PoN Convertible Mains (lugs)	Main lugs
Rated Current	125 A
Number of Spaces	2
Max Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	2
Maximum Number of Tandem Breakers	0
Number of Phases	1 phase
Wire Size	AWG 14...AWG 4 copper AWG 12...AWG 2 aluminium
Wiring Configuration	2-wire
Height	4.21 in (107 mm)
Width	2.52 in (64 mm)
Depth	1.34 in (34 mm)

Environment

Enclosure Rating	NEMA 1 indoor
Product Certifications	UL Listed

Ordering and shipping details

Category	US1DE3A00909
Discount Schedule	DE3A
GTIN	785901846918
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.80 in (9.65 cm)
Package 1 Width	8.90 in (22.61 cm)
Package 1 Length	12.60 in (32.0 cm)
Package 1 Weight	34.92 oz (990.0 g)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations