QON320L125I

Load center interior, QO, mounting base, 3 phase, 20 spaces, 125A main lugs, OEM, neutral busbar





Main

Marketing Trade Name	QO
Product Type	Mounting base

Complementary

PoN Convertible Mains (lugs)	Main lugs
Rated Current	125 A
Number of Spaces	20
Max Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	20
Maximum Number of Tandem Breakers	0
Number of Phases	3 phase
Wire Size	AWG 42/0 kcmil copper or aluminium
Wiring Configuration	4-wire

Environment

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	US1DE3A00909	
Discount Schedule	DE3A	
GTIN	785901558910	
Returnability	Yes	
Country of origin	US	

Packing Units

PCE	
1	
4.30 in (10.922 cm)	
12.80 in (32.512 cm)	
20.90 in (53.086 cm)	
10.00 lb(US) (4.536 kg)	
	1 4.30 in (10.922 cm) 12.80 in (32.512 cm) 20.90 in (53.086 cm)

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

18 months