



Pushing Performance  
Since 1945

## M5 3-pol st/- f/- PUR 2.0M



Part number	21 34 040 0312 020
Specification	M5 3-pol st/- f/- PUR 2.0M
HARTING eCatalogue	<a href="https://b2b.harting.com/21340400312020">https://b2b.harting.com/21340400312020</a>

### Identification

Category	System cabling
Series	Circular connectors M5
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	M5 A-coding Female Straight
Type of cable	Copper cable (round)

### Version

Cable length	2 m
Number of cores	3
Core structure	3x 0.25 mm <sup>2</sup>
Coding	A-coding

### Technical characteristics

Limiting temperature	-25 ... +80 °C
----------------------	----------------

### Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Black
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50



**Pushing Performance**  
Since 1945

## Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	567c8b78-5fa0-43aa-a4c0-beb9d99b7769
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Approvals	CE
-----------	----

## Commercial data

Packaging size	1
Net weight	50 g
Country of origin	Germany
European customs tariff number	85444290
GTIN	5713140283435
ETIM	EC001855
eCl@ss	27060311 Assembled sensor actuator-line