

Part Number: 1200110033

Product Description: Micro-Change (M12) Receptacle, 5 Poles, M12x1 and M14x1 Mounting Threads, Female (Straight) to Leads, 0.30m (11.81") Length

Series Number: 120011

Status: Active

Product Category: Circular Industrial

Connectors

Engineering Number: 8R5E30E03C3003



Documents & Resources

Drawings

Drawing 1200110033_sd.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	<u> </u>
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Contains Lead per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Circular Industrial Connectors
Series	120011
Description	Micro-Change (M12) Receptacle, 5 Poles, M12x1 and M14x1 Mounting Threads, Female (Straight) to Leads, 0.30m (11.81") Length
IP Rating	IP67
NEMA Rating	NEMA 6
Product Family	Brad Micro-Change (M12) Connectors
Product Name	Micro-Change (M12)
Туре	Single Ended (pigtail)
UPC	883906175528

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

Physical

Coupling Type	Internal Thread
Gender	Female
Keyway	Single
Length	0.30m
Material - Component	Nickel-plated Brass
Mounting Thread Size	M14 x 1.0
Net Weight	25.510/g
Orientation	Straight
Panel Mount	Front
Poles	5

Temperature Range - Operating	-20° to +80°C
Wire/Cable Type	Leads, UL 1061
Wire Size (AWG)	22

This document was generated on Apr 08, 2024