

Part Number: 1300480161

Product Description: Micro-Change (M12) Double-Ended Cordset, 4 Poles, Male (90°) to Male (90°), 24 AWG, PVC Cable, 1.0m (3.28')

Length

Status: Active

Engineering Number: E11A06303M010

Series Number: 130048

Product Category: Circular Industrial

Cordsets

Documents & Resources

Drawings

Drawing 1300480161_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | Not Reviewed per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Not Reviewed per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS | Not Reviewed per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------------|---|
| Category | Circular Industrial Cordsets |
| Series | 130048 |
| Description | Micro-Change (M12) Double-Ended Cordset, 4 Poles, Male (90°) to Male (90°), 24 AWG, PVC Cable, 1.0m (3.28') Length |
| IP Rating | IP67 |
| Performance Category | 5e |
| Product Family | Brad Industrial Ethernet Solutions |
| Product Name | Micro-Change (M12) |
| Protocol | N/A |
| Region | America, Asia, Europe |
| Type | Double Ended |
| UPC | 78172553199 |

Agency

| UL | E200650 |
|----|---------|
|----|---------|

Electrical

| Current - Maximum per Contact | 1.5A |
|-------------------------------|------|
| Voltage - Maximum | 30V |

Physical

| 5.59mm (.220") |
|--------------------|
| 1.0m (3.28') |
| Teal |
| Micro-Change (M12) |
| Micro-Change (M12) |
| Threaded |
| Male-Male |
| D-Coded |
| No |
| PVC |
| PVC |
| |

| Material - Contact | Copper Alloy |
|-------------------------------|---------------------|
| Material - Coupling Nut | Nickel-plated Brass |
| Material - Plating Mating | Gold |
| Orientation | 90° to 90° |
| Poles | 4 |
| Temperature Range - Operating | -20° to +75°C |
| Wire/Cable Type | N/A |
| Wire Size (AWG) | 24 |

This document was generated on Apr 14, 2024