
2273055-1 - ACTIVE

TE Internal #: 2273055-1 M12 Pigtail Cable Assembly, 5 Position, .2 m, Sensor/Actuator, Code A, M12 Socket, Single Ended, Plastic View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies



M8/M12 Application Type: Sensor/Actuator

Number of Positions: 5

Connector & Keying Code: A

Connector Type (End A): M12 Socket

Cable Assembly Type: M12 Pigtail

Features

Product Type Features

Connector Type (End A)	M12 Socket	
	WITZ JUCKEL	
Cable Assembly Type	M12 Pigtail	
Configuration Features		
Number of Positions	5	

Electrical Characteristics

Operating Voltage	125 VAC
Body Features	
Connector Color (End A)	Blue
Jacket Material	PUR
Wire Color (Base)	Brown, White, Blue, Black, Gray
Connector & Keying Code	A
Contact Features	
Contact Current Rating (Max)	4 A
Mechanical Attachment	
Thread Size	M12
Connector Orientation (End A)	Straight
Housing Features	
Housing Material	Plastic
Dimensions	

C For support call+1 800 522 6752

2273055-1

M12 Pigtail Cable Assembly, 5 Position, .2 m, Sensor/Actuator, Code A, M12 Socket, Single Ended, Plastic



Outside Cable Diameter	3.4 mm[.133 in]
Wire Size	.326 mm ²
Usage Conditions	
Operating Temperature Range	-40 – 80 °C[-40 – 176 °F]
Operation/Application	
M8/M12 Application Type	Sensor/Actuator
Shielded	No
Packaging Features	
Packaging Method	Box
Other	
Field Serviceable	Yes
Cable Assembly Length	.2 m
Cable Assembly Configuration	Single Ended

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

2273055-1

M12 Pigtail Cable Assembly, 5 Position, .2 m, Sensor/Actuator, Code A, M12 Socket, Single Ended, Plastic



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





Documents

Product Drawings

M12 Female pnl Mld Rear Mt PG9 pigt A

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_2273055-1_A.2d_dxf.zip English

Customer View Model

ENG_CVM_CVM_2273055-1_A.3d_igs.zip

2273055-1

M12 Pigtail Cable Assembly, 5 Position, .2 m, Sensor/Actuator, Code A, M12 Socket, Single Ended, Plastic



English

Customer View Model ENG_CVM_CVM_2273055-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages M8 / M12 Connector System Catalog

English

Product Specifications Product Specification

English