



Part Number : 1300350061

Series Number : 130035

Product Category : Industrial Tees and Splitters

Product Description : DeviceNet Power Monitor Tee, with LED Functionality, Female to Male

Status : Active


Engineering Number : DN3020PM-3

Documents & Resources

Drawings
Drawing 1300350061_sd.pdf

Product Environment Compliance

Compliance

| | |
|--------------------|--|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Contains Medium-chain chlorinated paraffins (MCCP); Lead; Tris(2-chloroethyl) phosphate; Dibutylphthalate per per D(2022)9120-DC (17 Jan 2023) |
| EU RoHS | Not Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|---|
| Status | Active |
| Category | Industrial Tees and Splitters |
| Series | 130035 |
| Description | DeviceNet Power Monitor Tee, with LED Functionality, Female to Male |
| IP Rating | IP67 |
| Product Family | DeviceNet Solutions |
| Product Name | DeviceNet Trunk |
| Type | Diagnostic Tee |
| UPC | 78172554891 |

Agency

| | |
|----|---------|
| UL | E152210 |
|----|---------|

Electrical

| | |
|-------------------------------|--------|
| Current - Maximum per Contact | 8.0A |
| Voltage - Maximum | 30V DC |

Physical

| | |
|---------------------------|--------------------------|
| Color - Cable Jacket | Gray |
| Drop Connector | Mini-Change |
| Drop Gender | Female |
| Keyway | Single |
| LED Indicator | Blue, Green, Red, Yellow |
| Left Trunk Connector | Mini-Change |
| Left Trunk Gender | Female |
| Leg 1 Length | N/A |
| Leg 2 Length | N/A |
| Material - Cable Jacket | N/A |
| Material - Connector Body | TPE |
| Material - Coupling Nut | Zinc Die-Cast |
| Net Weight | 844.000/g |

| | |
|-------------------------------|----------------|
| Poles | 5 |
| Right Trunk Connector | Mini-Change |
| Right Trunk Gender | Male |
| Temperature Range - Operating | -20°C to +80°C |