PXP6011/04P/CR/0405 Datasheet



Product Name // Inline Cable Connector PXP6011 Series 4 Contact Plug Crimp/Solder Termination (contacts available separately) 4mm-5mm Cable (Dark Grey Gland) Plastic Body







// Product Description:

- O Inline Cable Connectors
- Water and dustproof to IP66, IP68, IP69K when mated with compatible connector
- 30 degree push twist locking, tamperproof lock prevents accidental un-mating
- O Plug
- O 4 Contacts
- Crimp/solder termination with contacts and fitting tool available separately
- O Plastic Body
- O Cable acceptance 4mm-5mm diameter
- Gland Pack PXP6088 available separately to accommodate all sizes
- PXP6082 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with PXP6010 Series Flex Connectors

// General Information:

Product Display Title:

Product Family:

Product Series: Body Colour:

Body Material:

Body Material Type:

Contact Type:

Coupling Type: Current Max:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function: Insulation

Insulation Resistance:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Contact Accomodation Awg:

Min Contact Accomodation Awg:
Max Contact Accomodation Mm2:
Min Contact Accomodation Mm2:
Max Operating Temperature:
Min Operating Temperature:
Number Of Contacts:
Rohs Compliant:

Salt Spray Corrosion Test:

Voltage Max:

Inline Cable Connectors

Circular Power Connectors 6000 Series Buccaneer

Grey

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body Plug Contact Push-Twist 10A, 4A, 7A 32mm

UL94V-0

Inline Cable Connector >106MΩ @500V DC

IP66, IP68, IP69K

5mm 4mm 20AWG 16AWG 1.5mm2 0.5mm2 +120°C -40°C

4 Contacts

Yes EN60068-2-52 Test Kb Salt Mist (Cyclic) Marine Severity Level 1

277V

// Product PDF Links

6000 Series power connectors...

6000 Series metal body power...

// Product 3D CAD Model Links

PXP6011/04P/CR/04053D CAD Model