

M23 P HBM Back M25x1,5



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 15 600 0308 |
| Specification | M23 P HBM Back M25x1,5 |
| HARTING eCatalogue | https://b2b.harting.com/09156000308 |

Identification

| | |
|-----------------------------|---------------------------|
| Category | Hoods/Housings |
| Series | Circular connectors M23 |
| Identification | Power |
| Type of hood/housing | Bulkhead mounted housing |
| Description of hood/housing | Straight Rear mounting |

Version

| | |
|--------------|--|
| Size | M23 |
| Fixing | Thread M25 x 1.5 |
| Locking type | Screw locking ComLock rapid locking |

Technical characteristics

| | |
|--|--|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP67 locked condition IP69 / IPX9K acc. to ISO 20653 locked condition |

Material properties

| | |
|-------------------------|-------------------|
| Material (hood/housing) | Copper-zinc alloy |
| Surface (hood/housing) | Nickel plated |
| Material (seal) | NBR |
| Colour (seal) | Black |
| RoHS | compliant |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|----------------------|
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| | |
|----------|-----------------------|
| UL / CSA | UL 1977 ECBT2.E235076 |
|----------|-----------------------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 5 |
| Net weight | 46.3 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140184367 |
| ETIM | EC003556 |
| eCl@ss | 27440224 Shell for circular connectors |