

M12 housing male frontmounting packed



Part number	21 03 301 1001
Specification	M12 housing male frontmounting packed
HARTING eCatalogue	https://b2b.harting.com/21033011001

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Accessories
Series	Circular connectors M12
Type of accessory	Housing
Description of the accessory	for front mounting
Version	
Gender	Male
Technical characteristics	
Tightening torque	2 Nm Lock nut
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Material properties	
Material properties RoHS	compliant with exemption
	compliant with exemption 6(c): Copper alloy containing up to 4 % lead by weight
RoHS	
RoHS RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
RoHS RoHS exemptions ELV status	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption
RoHS RoHS exemptions ELV status China RoHS	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption 50
RoHS RoHS exemptions ELV status China RoHS REACH Annex XVII substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption 50 Not contained
RoHS RoHS exemptions ELV status China RoHS REACH Annex XVII substances REACH ANNEX XIV substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption 50 Not contained Not contained
RoHS RoHS exemptions ELV status China RoHS REACH Annex XVII substances REACH ANNEX XIV substances REACH SVHC substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption 50 Not contained Not contained Yes

Page 1 / 2 | Creation date 2023-12-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Material properties

California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26
Commercial data	
Packaging size	10
Net weight	15.3 g
Country of origin	Romania
European customs tariff number	85389099
GTIN	5713140137516
ETIM	EC002943
eCl@ss	27440292 Connector component (accessories)