

### AMP | AMP CPC

TE Internal #: 206153-2

Circular Power Connectors, Housing, 600 VDC, Wire-to-Wire, 4 Position, Sealable, Wire & Cable, Receptacle, Pin, Power & Signal,

Black, AMP CPC

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors > Circular Connector, Environmentally Sealed, CPC Series 6











Connector Product Type: Housing

Operating Voltage: 600 VDC

Connector System: Wire-to-Wire

Number of Positions: 4

Sealable: Yes

All Circular Connector, Environmentally Sealed, CPC Series 6 (19)

# **Features**

# **Product Type Features**

| Connector Seal & Plug Type        | Peripheral   |
|-----------------------------------|--------------|
| Connector Product Type            | Housing      |
| Connector System                  | Wire-to-Wire |
| Sealable                          | Yes          |
| Connector & Contact Terminates To | Wire & Cable |
| Connector & Housing Type          | Receptacle   |
| Circular Connector Shell Type     | All Plastic  |

# **Configuration Features**

| Reverse Numbering          | Without |
|----------------------------|---------|
| Number of Positions        | 4       |
| Number of Power Positions  | 0       |
| Number of Signal Positions | 4       |



# **Electrical Characteristics**

| Operating Voltage   | 600 VAC  |
|---|--|
| Contact Features  |  |
| Reverse Gender  | No   |
| Contact Type  | Pin  |
| Contact Protection  | With   |
| Mechanical Attachment   |  |
| Mating Alignment Type   | Keyed  |
| Mating Alignment  | With   |
| Mating Retention Type   | Threaded Coupling  |
| Thread Size   | 5/8-24 UNEF-2A   |
| Polarization Code   | A  |
| Connector Mounting Type   | Cable Mount (Free-Hanging)   |
| Mating Retention  | With   |
| Panel Mount Feature   | Without  |
|   |  |
| Housing Features  |  |
| Housing Features  Body Orientation  | Straight   |
|   | Straight<br>Black  |
| Body Orientation  |  |
| Body Orientation  Housing Color   | Black  |
| Body Orientation  Housing Color  Housing Material   | Black  |
| Body Orientation  Housing Color  Housing Material  Circular Connector Shell Size  | Black  |
| Body Orientation  Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  | Black Nylon 11   |
| Body Orientation  Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range   | Black  Nylon  11  -55 - 105 °C[-67 - 221 °F]                             |
| Body Orientation  Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance   | Black  Nylon  11  -55 - 105 °C[-67 - 221 °F]                             |
| Body Orientation  Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance  Operation/Application  | Black  Nylon  11  -55 - 105 °C[-67 - 221 °F]  Immersion                  |
| Body Orientation  Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance  Operation/Application  Circuit Application   | Black Nylon  11  -55 - 105 °C[-67 - 221 °F]  Immersion  Power & Signal   |
| Body Orientation  Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance  Operation/Application  Circuit Application  Shielded   | Black Nylon  11  -55 - 105 °C[-67 - 221 °F]  Immersion  Power & Signal   |
| Body Orientation  Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance  Operation/Application  Circuit Application  Shielded  Industry Standards                         | Black Nylon  11  -55 - 105 °C[-67 - 221 °F] Immersion  Power & Signal No |
| Body Orientation  Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance  Operation/Application  Circuit Application  Shielded  Industry Standards  UL Flammability Rating | Black Nylon  11  -55 - 105 °C[-67 - 221 °F] Immersion  Power & Signal No |



# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.  |
| Solder Process Capability                     | Not applicable for solder process capability  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts




















# Also in the Series | AMP CPC



Circular Power Connectors(458)



Connector Backshells(1)



Connector Caps & Covers(19)



Connector Contacts(6)



Connector Hardware(12)



Connector Seals & Cavity Plugs(36)



Connector Strain Relief(60)



Insertion & Extraction Tools(1)



Sealing Sleeves(2)

# Customers Also Bought



TE Part # 206060-1 CPC PLUG ASSEMBLY SIZE 11-4



TE Part # 206903-2 SEALING CAP ASSY,SZ 11,CPC



TE Part # 1-206062-4 CPC Cable Clamps



TE Part # 640706-2 CONTACT .045 POST PT BRASS



TE Part # 206430-4
CPC RECPT ASSEMBLY SIZE 11-4



TE Part # 807079-000 382A023-4/42-0



WLAN DUAL BAND ANTENNA FPC V 100 MHF4 TY







### **Documents**

# **Product Drawings**

**CPC RECPT ASSEMBLY SIZE 11-4** 

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_206153-2\_V.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_206153-2\_V.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_206153-2\_V.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

# Datasheets & Catalog Pages

AMP Circular Connectors for Commercial Signal & Power Applications

English

# **Product Specifications**

**Application Specification** 

English

# Agency Approvals

**UL Report** 

English