

BUSHING

2X SCREW AND LOCK WASHER

BACKSHELL

2X LATCH SEGMENT

2X RECOMMENDED TORQUE: 1.5-2.0 NM-


1. RECEPTACLE MATERIAL: SHELL: ZINC ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC SEAL: SILICONE RUBBER


NOTES: UNLESS OTHERWISE SPECIFIED

2. BACKSHELL MATERIAL:

SHELL: ALUMINIUM ALLOY, NICKEL PLATED: LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL; BUSHING: EPDM.

- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
 - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.6 RoHS COMPLIANT
- 4. APPLY TO CABLE OD SIZE: Ø11.20-Ø24.08 . CAN BE USED:
 - 4.1. WITH LARGE AND SMALL BUSHINGS IN PLACE.
- 4.2. WITH ONLY LARGE BUSHING IN PLACE.
- 4.3. WITH BOTH BUSHINGS REMOVED.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC RECEPTACLE DRAWING FOR:
 - 6.1 CONTACT SIZE AND WIRE RANGE.
 - 6.2 RETAINING RING COLOR.
 - 6.3 MATING PART(S).
 - 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.





AHDM04-24-18PR-059 HD34-24-18PE-059 PART NUMBER DESCRIPTION ITEM QUANTITY MATERIALS LIST UNLESS OTHERWISE SPECIFIED SIGNATURES DATE Amphenol J. HEAD 16MAR2020 Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MJ 48036 MATERIAI SPECIFICATIONS CUSTOMER: DURAMATE AHDM RECEPT, SIZE 24, WD THD, THIS DRAWING IS SUPPLED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DA'S SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHOUS THE AMPHENOL NO PROPER TO PROPER TO PROPER THE PROPERTO OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. KIT W/ CABLE CLAMP BACKSHELL PROCESS SPECIFICATIONS B C-AHDM04-24-18PR-059 NEXT ASS'Y CALE: NONE SHEET 1 OF 1

REV: A1 SH:

KIT, RECPT AND BACKSHELL, SZ 24

DWG NO:

A Series™ - Contact Size 8 Options (Works with: ATHD and DuraMate Series)

| Machined Contacts, Pins and Sockets | | | | | |
|-------------------------------------|--|------|------|----------|------|
| Part Number | Description | Size | AWG | Туре | Amps |
| AT60-204-08141 | Male Contact - Pin, Copper Alloy, Nickel-Plated | 8 | 8-10 | Machined | 60A |
| AT62-203-08141 | Female Contact - Socket, Copper Alloy, Nickel-Plated | 8 | 8-10 | Machined | 60A |
| AT60-204-08141-16 | Male Contact - Pin, Copper Alloy, Nickel-Plated | 8 | 6 | Machined | 60A |
| AT62-203-08141-16 | Female Contact - Socket, Copper Alloy, Nickel-Plated | 8 | 6 | Machined | 60A |

| | Tooling - Machined Contacts | |
|-------------|---|--|
| Part Number | Description | |
| WA23 | Heavy Duty Pneumatic Crimp Tool -Uses Universal Positioner Part No. WA23-101DA and Crimp Locator MFX-3961 | |
| WA23-2 | Die Assembly -for CA-5E12 Heavy Duty Pneumatic Crimp Tool, Size 8 | |
| WA23-3 | Die Assembly -for CA-5E12 Heavy Duty Pneumatic Crimp Tool, Size 6 | |
| WA23-10 | Contact Locator, Size 6 and Size 8 | |
| 96-978-22 | Crimper and Dies -for Size 10mm²-185mm² Wires | |
| AT114008 | Contact Removal Tool, Plastic, Size 8, 8-10AWG | |

A Series™ - Contact Size 12 Options (Works with: AHD-6, ATP, ATHD, DuraMate and PanelMate Series)

| | Machined Contacts, Sockets & Pins | | | |
|--------------------|--|------|-------|----------|
| Part Number | Description | Size | AWG | Туре |
| *AT60-204-12141-10 | Male Contact - Pin, Nickel-plated | 12 | 10-12 | Machined |
| *AT62-203-12141-10 | Female Contact - Socket, Nickel-plated | 12 | 10-12 | Machined |
| AT60-220-1231 | Male Contact - Pin, Gold-plated | 12 | 12-14 | Machined |
| AT62-210-1231 | Female Contact - Socket, Gold-plated | 12 | 12-14 | Machined |
| AT60-204-12141 | Male Contact - Pin, Nickel-plated | 12 | 12-14 | Machined |
| AT62-203-12141 | Female Contact - Socket, Nickel-plated | 12 | 12-14 | Machined |

^{*}Works with ATP Series only

| | • Smaller AWG fo | DiagnosticGrade™ Machined Contacts, Sockets & Pi or Diagnostic Applications • Gold-plated • Increased Matin | | es • Cost-e | effective |
|---|--------------------|--|------|-------------|-----------|
| | Part Number | Description | Size | AWG | Туре |
| Γ | 65-54749 | Male Contact - DiagnosticGrade™, Pin, Gold-plated | 12 | 20 | Machined |
| | AT62-210-1231-1820 | Female Contact - DiagnosticGrade™, Socket, Gold-plated | 12 | 20 | Machined |

| Tooling - Machined Contacts | | |
|-----------------------------|--|--|
| Part Number | Description | |
| AUTK-12 | Hand Crimp Tool, Size 12 | |
| AUTK-100 | Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20 | |
| CA-5D12 | Universal Hand Crimp Tool, Size 12/16/20 | |
| CA-5E12 | Pneumatic Crimp Tool, Size 12/16/20 | |
| M300-25A | Hand Crimp Tool used with Crimp Locator MFX-3966, Size 12, 10AWG | |
| MFX-3966 | Contact Locator used with Hand Crimp Tool M300-25A, Size 12, 10AWG | |

| Con | Contact Removal Tools (For both Machined or Stamped & Formed Contacts) | | |
|---------------|--|--|--|
| Part Number | Part Number Description | | |
| ATRT-100 | Contact and Wedgelock Extraction Tool | | |
| AT11-337-1205 | Contact Removal Tool, Plastic, Size 12 | | |

| | Sealing Plugs (For both Machined or Stamped & Formed Contacts) | | |
|-------------|--|--|--|
| Part Number | Part Number Description | | |
| A114017 | Sealing Plug, Size 12, White | | |

| Stamped & Formed Contacts, Sockets & Pins | | | | |
|---|--|------|-------|------------------|
| Part Number | Description | Size | AWG | Туре |
| AT60-12-0244 | Male Contact - Pin, Gold-plated | 12 | 10-12 | Stamped & Formed |
| AT62-12-0244 | Female Contact - Socket, Gold-plated | 12 | 10-12 | Stamped & Formed |
| AT60-12-0222 | Male Contact - Pin, Nickel-plated | 12 | 10-12 | Stamped & Formed |
| AT62-12-0222 | Female Contact - Socket, Nickel-plated | 12 | 10-12 | Stamped & Formed |
| AT60-12-0144 | Male Contact - Pin, Gold-plated | 12 | 12-14 | Stamped & Formed |
| AT62-12-0144 | Female Contact - Socket, Gold-plated | 12 | 12-14 | Stamped & Formed |
| AT60-12-0166 | Male Contact - Pin, Nickel-plated | 12 | 12-14 | Stamped & Formed |
| AT62-12-0166 | Female Contact - Socket, Nickel-plated | 12 | 12-14 | Stamped & Formed |

| | Tooling - Stamped & Formed Contacts | | |
|-------------|---|--|--|
| Part Number | Description | | |
| MFX-3973 | Crimp Die - Size 12 | | |
| MFX-3985 | Crimp Die - Svize 12, 10-12AWG -02XX Series | | |
| ATT-12-00 | Hand Crimp Tool - Size 12, 12AWG | | |
| ATT-12-01 | Hand Crimp Tool - Size 12, 10AWG | | |

A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

| | Machined Contacts, Sockets & Pins | | | |
|-------------------|--|------|-------|----------|
| Part Number | Description | Size | AWG | Туре |
| AT60-215-1631 | Male Contact - Pin, Gold-plated | 16 | 14 | Machined |
| AT62-209-1631 | Female Contact - Socket, Gold-plated | 16 | 14 | Machined |
| AT60-215-16141 | Male Contact - Pin, Nickel-plated | 16 | 14 | Machined |
| AT62-209-16141 | Female Contact - Socket, Nickel-plated | 16 | 14 | Machined |
| AT60-202-1631 | Male Contact - Pin, Gold-plated | 16 | 16-20 | Machined |
| AT62-201-1631 | Female Contact - Socket, Gold-plated | 16 | 16-20 | Machined |
| AT60-202-16141 | Male Contact - Pin, Nickel-plated | 16 | 16-20 | Machined |
| AT62-201-16141 | Female Contact - Socket, Nickel-plated | 16 | 16-20 | Machined |
| AT60-202-1631-22 | Male Contact - Pin, Gold-plated | 16 | 22-24 | Machined |
| AT62-201-1631-22 | Female Contact - Socket, Gold-plated | 16 | 22-24 | Machined |
| AT60-202-16141-22 | Male Contact - Pin, Nickel-plated | 16 | 22-24 | Machined |
| AT62-201-16141-22 | Female Contact - Socket, Nickel-plated | 16 | 22-24 | Machined |

| | Tooling - Machined Contacts | | |
|-------------|---|--|--|
| Part Number | Description | | |
| AUTK-16 | Hand Crimp Tool, Size 16 | | |
| AUTK-100 | Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20 | | |
| CA-5D12 | Universal Hand Crimp Tool, Size 12/16/20 | | |
| CA-5E12 | Pneumatic Crimp Tool, Size 12/16/20 | | |

| Contact Removal Tools (For both Machined or Stamped & Formed Contacts) | | |
|--|--|--|
| Part Number | Description | |
| ATRT-100 | Contact and Wedgelock Extraction Tool | |
| AT11-310-1605 | Contact Removal Tool, Plastic, Size 16 | |

| Sealing Plugs (For both Machined or Stamped & Formed Contacts) | | | | |
|--|---|--|--|--|
| Part Number | Description | | | |
| A114017 | Sealing Plug, Size 16, White | | | |
| A114017-SR | Sealing Plug, Size 16, SR01 Series, Black | | | |
| AT13-217-1605 | Locking Sealing Plug, Size 16, Grey | | | |
| AT13-217-1605-SR | Locking Sealing Plug, Size 16, SR01 Series, Red | | | |

| Stamped & Formed Contacts, Sockets & Pins | | | | | |
|---|--|------|-------|------------------|--|
| Part Number | Description | Size | AWG | Туре | |
| AT60-14-0122 | Male Contact - Pin, Nickel-plated | 16 | 14-18 | Stamped & Formed | |
| AT62-14-0122 | Female Contact - Socket, Nickel-plated | 16 | 14-18 | Stamped & Formed | |
| AT60-14-0144 | Male Contact - Pin, Gold-plated | 16 | 14-18 | Stamped & Formed | |
| AT62-14-0144 | Female Contact - Socket, Gold-plated | 16 | 14-18 | Stamped & Formed | |
| AT60-16-0122 | Male Contact - Pin, Nickel-plated | 16 | 16-18 | Stamped & Formed | |
| AT62-16-0122 | Female Contact - Socket, Nickel-plated | 16 | 16-18 | Stamped & Formed | |
| AT60-16-0144 | Male Contact - Pin, Gold-plated | 16 | 16-18 | Stamped & Formed | |
| AT62-16-0144 | Female Contact - Socket, Gold-plated | 16 | 16-18 | Stamped & Formed | |
| AT60-16-0622 | Male Contact - Pin, Nickel-plated | 16 | 16-20 | Stamped & Formed | |
| AT62-16-0622 | Female Contact - Socket, Nickel-plated | 16 | 16-20 | Stamped & Formed | |
| AT60-16-0644 | Male Contact - Pin, Gold-plated | 16 | 16-20 | Stamped & Formed | |
| AT62-16-0644 | Female Contact - Socket, Gold-plated | 16 | 16-20 | Stamped & Formed | |
| AT60-16-0677 | Male Contact - Pin, Tin-plated | 16 | 16-20 | Stamped & Formed | |
| AT62-16-0677 | Female Contact - Socket, Tin-plated | 16 | 16-20 | Stamped & Formed | |
| AT60-16-0822 | Male Contact - Pin, Nickel-plated | 16 | 20-22 | Stamped & Formed | |
| AT62-16-0822 | Female Contact - Socket, Nickel-plated | 16 | 20-22 | Stamped & Formed | |
| AT60-16-0844 | Male Contact - Pin, Gold-plated | 16 | 20-22 | Stamped & Formed | |
| AT62-16-0844 | Female Contact - Socket, Gold-plated | 16 | 20-22 | Stamped & Formed | |

| Tooling - Stamped & Formed Contacts | | | |
|-------------------------------------|-------------------------------------|--|--|
| MFX-3950 | Crimp Die - Size 16, 18-20AWG | | |
| MFX-3953 | Crimp Die - Size 16, 16-18AWG | | |
| MFX-3975 | Crimp Die - Size 16, 14-16AWG | | |
| MFX-3990 | Crimp Die - Size 16, 20-22AWG | | |
| ATT-16-00 | Hand Crimp Tool - Size 16, 14-16AWG | | |
| ATT-16-01 | Hand Crimp Tool - Size 16, 18-20AWG | | |
| ATT-1612-03 | Hand Crimp Tool - Size 16, 20-22AWG | | |